



The State of New Hampshire
DEPARTMENT OF ENVIRONMENTAL SERVICES



Thomas S. Burack, Commissioner

December 10, 2010

Jake Dawson
Lakes Region Water Company, Inc.
P.O. Box 389
Moultonboro, NH 03254-0389

**RE: Moultonboro – West Point (EPAID: 1612040)
Water Conservation Plan, October 30, 2010, NHDES #999453**

Dear Mr. Dawson:

The New Hampshire Department of Environmental Services (“Department”) has completed its review of the Water Conservation Plan (WCP) submitted by Lakes Region Water Company, Inc. for the West Point small community water system in Moultonboro, NH. The plan was received on November 3, 2010 and submitted to fulfill the requirements of Env-Wq 2101, *Water Conservation Rules*.

Public notification was initiated on November 10, 2010. Entities had an opportunity to provide comment on the plan until December 3, 2010. The Department did not receive any comments from either the Town of Moultonboro or the Lakes Region Planning Commission during the required 21-day waiting period. The public notification requirement has been met.

The purpose of this letter is to conditionally approve the draft Water Conservation Plan dated October 30, 2010. The Department makes the following conditional requirement:

Source Meters: The WCP states that there will be one source meter for all of the wells as the system is a blended source. However the Department requires that each source be individually metered.

- Source meters need to be installed to measure flow from each of the three wells: the two active well sources and the new source in this case. These meters need to be installed in the system before the blending point and in accordance with the procedures and protocols described in the American Water Works Association (AWWA) 1999 document M6, *Manual of Water Supply Practices: Water Meters – Installation, Testing, and Maintenance.*”

Every three years from this date of approval, the water system shall supply the Department with documentation of compliance with the plan. This information shall be supplied on a form provided by the Department and shall include contact information for the water system owner and the person responsible for carrying out the tasks of the plan, all data relating to meter reading, water audits, leak detection, public outreach, and the dates these tasks were performed.

If you have any questions about this letter or any other water conservation issues please feel free to call me at **271-0659** or email me at ernst.kastning@des.nh.gov

Sincerely,

A handwritten signature in black ink, appearing to read "Ernst H. Kastning". The signature is written in a cursive style with a large, stylized initial "E".

Ernst H. Kastning
Drinking Water and Groundwater Bureau

Ec: Derek Bennett, NHDES - DWGB
Cc: Mr. Thomas Mason, Jr., Lakes Region Water Company, Inc.

Report Form for Water Conservation Plans Small Community Water Systems

PROJECT NAME: West Point – Small Community Water System
TOWN/CITY: Moultonboro, NH
EPA ID # 1612040
DATE: October 30, 2010

PURPOSE A community water system seeking approval for a new source of water must meet the requirements of New Hampshire Administrative Rule Env-Wq 2102, Water Conservation. Requirements vary depending on the type of water system as follows: **Env-Wq 2101.06 Existing Small Community Water System**

This report was submitted for review to:

ATTN: Derek Bennett
NHDES – Drinking Water & Groundwater Bureau
29 Hazen Drive, PO Box 95
Concord, NH 03302-0095

PROJECT/CONTACT INFORMATION

The Preliminary Well Siting report is being submitted concurrently to the NHDES for review.


Project Contact:

Name: Jake Dawson
Address: PO Box 389, Moultonboro, NH 03254
Company: Lakes Region Water Company Inc.
Phone Number: (603) 476-2348 or cell (603) 677-6478

Project Owner:

Name: Thomas Mason Jr.
Address: PO Box 389, Moultonboro NH 03254
Company: Lakes Region Water Company Inc.
Phone Number: (603) 476-2348

To the best of our knowledge, ownership of the water system will NOT be transferred at a future date from the person listed above to a homeowner's association or any other entity.



SOURCE & SYSTEM OVERVIEW

- **Reason for New Source:** As stated in the West Point Preliminary Well Siting Report, Reclaimed BRW #3 will be used to supplement declining yields of existing system wells. During the summer 2010, the West Point CWS began “running out of water” during times of peak demand. Peak demand is realized during the summer months, especially during the busy July 4th, Labor Day, and Memorial Day holiday weekends. LRWC had to truck in outside water several times this past summer in attempts to keep up with the demands of the system.
- **Service Connections/Types:** The West Point CWS consists of 42 existing service connections, all of which are residential homes. There are NO known industrial, commercial, institutional, or municipal connections. None of these service connections receive more than 20,000 gpd as they are used as single family homes. There are an estimated 8 additional service connections that could exist at full build-out. This is the maximum number of services that could be added in the future; however, there is no evidence to suggest that this would happen any time in the near future. Any new service connections that are added will have meters installed in a timely manner.
- **Population Trends:** The majority of the West Point customers are seasonal occupants. The summer months are when the system exhibits highest water use, because there is an increase in average occupants due to the seasonal nature of the system. The busiest times are during long holiday weekends, specifically the July 4th, Memorial Day and Labor Day holidays. The average daily use is usually less than 6,000 gpd, with maximum daily use of less than 13,000 gpd occurring during the busy July months, where peak use is realized and temperatures usually the highest. Maximum daily yields of each well source will be re-determined during the 48 hour pumping test to be performed following the Preliminary Well Siting Approval.

SYSTEM METERING

- **Water Sources:** There are 2 active well sources currently in use for the West Point CWS and 1 inactive well source that is currently in the process of approval. Each of these are drilled, bedrock wells. The active ones are named BRW #1 and BRW #2. We are currently seeking approval for Reclaimed BRW #3, which had collapsed 20± years ago, but was re-drilled during Mid-June 2010 to remove the collapse so as the source could be once again used.
- **Source Meters:** There is 1 source meter for all wells as the system is designed as a blended source. This meter is a 1” Sensus SR meters with flow ranges of 0 – 100 gpm. They blended source is typically read at least once a week, but they are always read at least once every 30 days. The last meter test date was in 2006, but we will continue to test once every 4 years as required by NHPUC rules and AWWA standards.

Source meters will continue to be selected, installed, tested, and maintained in accordance with the procedures and protocols described in the American Water Works Association (AWWA) 1999 document identification number M6, “Manual of Water Supply Practices, Water Meters- Selection, Installation, Testing, and Maintenance”.

- **Service Meters:** Each of the existing 42 West Point CWS customers are considered residential in nature and have Sensus SR 5/8" water meters currently installed. Any new service connections will have meters installed according as soon as possible; however, no new service connections have been recently added. We test according to AWWA and NHPUC rules, which requires a 5/8" meter to be tested no less than once every 10 years. Customer meters are read once every 90 days (once per quarter) using a Sensus Handheld AR5001 and Autogun for touch readings.

Service meters will continue to be selected, installed and maintained in accordance with "Manual of Water Supply Practices, Water Meters-Section, Installation, Testing, and Maintenance," document identification number AWWA M6, American Water Works Association, 1999.

WATER AUDITS & LEAK DETECTION

- **Estimated Unaccounted for Water:** Lakes Region Water Company Inc. estimates for unaccounted for water at least annually, but typically about once per quarter. We review customer meter records as compared to source meter records, taking into account any excess kilowatt hours used by the pump stations (2) and any customer complaints or insight that is available to help us identify any potential leaks. We also perform system inspections about once per week, noting any significant changes in activity and perform leak detection as necessary, but at least once per year. The most recent estimate of unaccounted for water was calculated in June 2010 in which 0.66 gpm was unaccounted for and considering lost due to leakage.

Lakes Region Water shall prepare and submit a response plan to the NHDES Water Conservation Department within 60 days anytime the percentage of unaccounted for water in the West Point CWS exceeds 15% of the total water introduced into the system, identifying how we intend to reduce the percentage to below 15% within 2 years or less.

- **Water Audits & Leak Detection:** The Company performs in-house leak detection, since several of their field personnel are certified water operators who have successfully completed training sessions of a wide variety conducted by NHDES, AWWA and Granite State Rural Water Association. As stated above, our most recent leak detection was performed in June 2010, where a small 0.66 gpm leak was discovered. 100% of the system was surveyed for leakage and 100% of the losses were recovered upon its immediate repair.

A Meter Master Flow Recorder (Model100 EL) is often used to record flows on a continuous basis, which are then analyzed to obtain minimum flows during off-peak hours (in the middle of the night), which is considered true water loss. This process typically occurs following an unaccounted for water estimate, but no less than once per year.

The West Point CWS is comprised of approximately 2,500 feet of 4" diameter PVC pipe, which was installed in the early 1970s. At least once every 2 years, all water mains, shut off valves, blow offs and customer service lines are completely surveyed for leakage using an acoustic listening device. A ground microphone is used in conjunction with acoustic listening device Models HL400 and HL 90 which are manufactured by Metrotech. Each of these contact points will be field surveyed for water leakage at 5 foot intervals over the top of the pipe.

Since this system has only 2500 feet of water main and an overall low consumption volume, it is not cost effective or necessary to install zone meters to assist in leak detection. At the conclusion of this assessment, any damages to existing structures will be noted and replaced as soon as possible, but no later than 60 days.

- **Intentional Water Loss:** There are no “bleeders” used within the system at dead ends to improve water quality or prevent freeze-ups because they are unnecessary. There are also no storage tanks that we allow to intentionally overflow due to unique system hydraulics or other concerns.
- **Pressure Management:** The West Point CWS currently operates at pressures between 40 psi and 60psi. Pressure reduction is not necessary because there are no zones that exceed maximum operating pressures allowed by State Rules. If the pressure exceeds 100 psi, pressure-reducing valves will be installed on the service line or water main to maintain the pressure below 100 psi.

Lakes Region Water will perform a water audit & leak detection in accordance with “Manual of Water Supply Practices, Water Audits & Leak Detection” document identification number AWWA M36, American Water Works Association, 1999. Any identified leaks will be documented & repaired immediately or within 60 days of discovery unless a waiver is obtained in accordance with Env-Wq 2101.09.

CONSUMPTION MANAGEMENT

- **Conservation Rate Structure:** West Point community water system is charged in accordance with our Company Tariff which is NHPUC approved. Each customer receives a quarterly water bill comprised of two (2) separate charges. The first is a minimum “base rate” that is charged to each customer per quarter regardless of how much water is used. In addition to this flat fee, each customer is charged for the total amount of water that passes through their individual water meter, which encourages judicious use of water. There are no seasonal rate structures in place, and the billing policies described above will remain in effect indefinitely.
- **Educational Outreach Initiative:** The educational outreach initiative will consist of two NHDES Fact Sheets (*attached*):
 - Fact Sheet WD-DWGB-26-2: Water Efficiency Practices for Domestic Indoor Water Use
 - Fact Sheet WD-DWGB-26-3: Water Efficiency Practices for Outdoor Water Use

These fact sheets are highly informative materials that can familiarize customers of simple water conservation measures that can be implemented at home. They will be distributed to each customer immediately following the department’s approval of the new source (most likely to be included along with customer’s quarterly water bills). After this initial mailing, they will be distributed annually along with the Consumer Confidence Report (CCR), which must be sent to each customer by July 1st of each year.

In order to document how compliance with the requirements of Env-Wq 2102 is being achieved, Lakes Region Water Company Inc. will submit a "3 Year Water Conservation Compliance Report" to be supplied by the NHDES once every three years. All activities outlined in this water conservation plan will be completed by water system personnel under the supervision of a certified water system operator.

- **Public Notification:** Within 7 days of submitting the final water conservation report to the NHDES for review, Lakes Region Water Company Inc. will provide via certified mail:
 - The Final Water Conservation Report (after initial NHDES review)
 - Education outreach materials for review:
 - Water Conservation Rules Summary (Env-Wq 2101)
 - NHDES Fact Sheet WD-DWGB-26-2: Water Efficiency Practices for Domestic Indoor Water Use
 - NDHES Fact Sheet WD-DWGB-26-3: Water Efficiency Practices for Outdoor Water Use

The materials listed above will be sent to the following governing boards:

- Lakes Region Planning Commission
103 Main Street, Suite 3
Meredith, NH 03253
- Marie Samaha, Chairperson
Town of Moultonboro, Conservation Commission
PO Box 139
6 Holland Street
Moultonboro, NH 03254

Copies of the cover letters to be sent to the governing boards along with all pertinent attachments are enclosed for NHDES review. Certified mail receipts will be provided when available.

Before submitting, thoroughly check this form to be sure all applicable questions are answered, all information is provided, and all necessary attachments are included. Incomplete submittals will significantly slow the approval process.

If strict compliance with any of the requirements of Env-Wq 2101 is not feasible, the small community water system may apply for a waiver to a specific portion of the rule. A waiver application form is provided at the end of this document for your convenience.

Preparer's Signature: _____

A handwritten signature in black ink, written over a horizontal line. The signature is stylized and appears to be a first name followed by a last name.

Date: **October 30, 2010**

As a reminder, have you included the following?

- Educational outreach initiative documentation and materials created by the water system.
- Public notification documentation (certified mail receipts).
- Public notification cover letters and pertinent documents.
- Other pertinent or supportive materials.

ATTACHMENTS

LAKES REGION WATER COMPANY INC.

420 Governor Wentworth Highway, PO Box 389
Moultonborough, NH 03254
Telephone: 603-476-2348, Fax: 603-476-2721
Hours: Monday through Friday, 8:30am to 4:30pm

November 1, 2010

Governing Board
Address
City, NH Zip code

Re: Water Conservation Plan for West Point Community Water System, Moultonboro NH

Dear _____:

Applicants applying for approval of new drinking water sources for Community Water Systems are subject to the requirements of Env-Wq 2101: *Water Conservation Rules*. As part of the application process we must complete a water conservation plan for the new water source and submit it for review by the New Hampshire Department of Environmental Services (NHDES). We must also perform the following Public Notification tasks:

- Provide a summary of Water Conservation Rule Env-Wq 2101 and the proposed water conservation plan for the water system to the governing board of the municipality in which the water system is located and the regional planning commission established for the area where the water system is located.
- Request that the governing board of each municipality review the water conservation plan for consistency with Env-Wq 2101 and amend the local site planning requirements to promote water conservation landscaping practices within the service area of the new water system.
- Request that the regional planning commission review the water conservation plan for consistency with Env-Wq 2101 and promote water conservation landscaping and other conserving water use practices among its member towns.

We are requesting that you review the enclosed materials, comment on the water conservation plan, and promote water conservation practices within your jurisdictional area. You have twenty-one (21) days to review and provide comment to NHDES on the water conservation plan. This 21-day period commences upon the receipt date of certified mailing of this correspondence. Please communicate your comments in writing to NHDES at your earliest convenience and address all comments to:

ATTN: Derek Bennett
NHDES-Drinking Water & Groundwater Bureau
29 Hazen Drive, PO Box 95
Concord, NH 03302

In addition, if you wish to review the preliminary well siting, you may contact the above NHDES staff at (603) 271-6685. Thank you in advance for your time and cooperation.

Sincerely,

Taryn Zambouras
Office Manager, Lakes Region Water Company Inc.
Water Conservation Plan Project Contact

Email: lrwater@lakesregionwater.com
Website: lakesregionwater.com

Draft Cover Letter to
Governing Boards

**-Water Conservation Rules-
Env-Wq 2101 (formerly Env-Ws 390)**

Applicants applying for permits to develop new sources of water need to be aware that they are subject to new water conservation requirements required by RSA 485.61 which became law in July 2002. The law requires that the Department of Environmental Services (Department) adopt and administer water conservation rules for applicants developing the following type of new water sources:

1. New sources of groundwater for community water systems subject to RSA 485:3;
2. New sources of groundwater for bottled and bulk water operations subject to RSA 485:3;
3. New sources of groundwater that exceed 57,600 gallons over any 24-hour period subject to RSA 485-C; and
4. New sources of surface water associated with projects that require a water quality certification pursuant to Section 401 of the Federal Clean Water Act.

The Department met with an advisory committee consisting of representatives of municipalities, community water systems, environmental organizations, and business and industry to develop the water conservation rules. The rules were formally adopted by the Department in May 2005.

A general summary of the requirements of the water conservation rules is provided below.

**Requirements for All Large Community Water Systems and All New Small
Community Water Systems Developing New Sources of Water**

1. Install and maintain meters for all water withdrawals and service connections.
2. Implement a water audit, leak detection and leak repair program in accordance with the "Manual of Water Supply Practices, Water Audits and Leak Detection", document identification number AWWA M36, American Water Works Association, 1999.
3. When applicable, development and implementation of response plans to reduce unaccounted for water to less than 15%.
4. Implement a rate structure that encourages efficient water use.
5. Implement a water conservation educational outreach initiative.

**Requirements for Existing Small Community Water Systems
Developing New Sources of Water**

1. Either: a) Install source and service connection meters and implement a water audit, leak detection and leak repair program in accordance with the "Manual of Water Supply Practices, Water Audits and Leak Detection", document identification number AWWA M36, American Water Works Association, 1999; or b) Complete a system-wide leak detection once every two years.
2. Repair all leaks within 60 days of identification.
3. Implement a water conservation educational outreach initiative.

**Requirements for Applicants Developing New Sources of Water for
Industrial, Commercial, or Institutional Water Uses**

1. Install water meters for all water sources.
2. Retrofit or replace single pass water-cooling systems when feasible based upon an economic analysis that includes a four-year payback period.
3. Install controls to stop the overflow or discharge of water to waste when feasible based upon an economic analysis that includes a four-year payback period.
4. Identify water conservation best management practices or best available technologies that may be applicable to the types of water-using processes at the subject facility, and implement these measures when feasible based upon an economic analysis that includes a four-year payback period.
5. For all new lawn areas, install six (6) inches of loam and devices to shut-off automatic irrigation systems when not needed.

For more information about the water conservation rules, contact Derek Bennett at 271-6685 or derek.bennett@des.nh.gov.

ENVIRONMENTAL Fact Sheet



29 Hazen Drive, Concord, New Hampshire 03301 • (603) 271-3503 • www.des.nh.gov

WD-DWGB-26-2

2010

Water Efficiency Practices for Domestic Indoor Water Use

Only 1 percent of the earth's water is available for drinking. The average American uses 100 gallons of water a day. Our excessive water use habits deplete potable drinking water supplies and return trillions of gallons of wastewater to streams and coastal waters. The following indoor water efficiency practices can save as much as 25,000 gallons of water per person per year. Water efficiency practices not only save water, they save money. For a description of how to determine water use in your home, see the following fact sheets at www.des.nh.gov/organization/commissioner/pip/factsheets/dwgb/index.htm and scroll to WD-DWGB-26-15, "Performing a Domestic Water Use and Conservation Audit." To save water on outdoor use, see fact sheet WD-DWGB-26-3, "Water Efficiency Practices for Outdoor Water Use" at the same website.

General Water Efficiency Practices

The following water efficiency practices apply to general domestic water use. Bathroom, kitchen and laundry water use are addressed in later sections.

- Look for the WaterSense label when considering water using fixtures, appliances, and services. WaterSense, sponsored by the U.S. Environmental Protection Agency (EPA), labels water-efficient products that have been independently tested to ensure water savings without sacrificing performance or quality.
- Shut off water when not in use, such as when you brush your teeth or shave.
- Never put water down the drain when you can use it for something else, such as watering plants.
- Insulate water pipes and hot water heaters. This retains heat so that water doesn't need to run as long to get hot. It also saves on energy costs.
- Avoid water softening systems unless absolutely necessary. Backwashing these systems uses large quantities of water. If you do use a water softener, run the minimum amount of recommended regenerations to maintain softness.
- Turn off pumps, water softeners, and other water-using equipment while on vacation.
- Check for and repair leaks. Not only will you save water but you will save energy and money. A large percentage of energy costs can be attributed to pumping, treating, heating, and cooling water.
- If you are on municipal water and have a meter at your house, check the meter over a period of time when no one is using water. If the meter moves, you have a leak.
- If you have a well, the pump shouldn't run at times when no water is being used.

Water Efficiency Practices in the Bathroom

More than one fourth of all domestic indoor water consumption is used in the bathroom. The following water efficiency practices will help you save water in the bathroom.

- Install ultra-low flow toilets (ULF) that use a maximum of 1.28 gal/flush (4.8L/flush) or retrofit existing toilets with displacement bottles or dams. Dual flush toilets offer a choice between the 1.6-gallon flush for solid wastes and a 1.0-gallon flush for liquid only. Never put bricks in toilet tanks; they disintegrate over time. Use a squat, fat glass jar, like a pickle jar, no more than 6" high, filled with water. Glass is heavier than plastic and less apt to shift around in the tank.
- Install low-flow bathroom faucets that use no more than 1.5 gallons per minute or install low-flow faucet aerators or laminar flow restrictors. These devices are readily available at most hardware and building supply stores.
- Install low-flow showerheads that use no more than 2.0 gallons per minute. Low-flow showerheads are designed to use less water and still provide the same invigorating spray as their water-wasting counterparts.
- Don't use the toilet as a garbage disposal. Avoid unnecessary toilet flushing by disposing of tissues, cigarette butts and other items in the trash, and composting vegetable food waste.
- Replace or repair toilet flush handles that stick in the flush position.
- Avoid using automatic bowl cleaners in your toilet tank. These chemicals rapidly degrade flapper valves and other tank components, causing the toilet to leak.
- Adjust the toilet tank float level so that water fills no higher than 0.5"-1.0" below the top of the overflow pipe. At higher levels water can flow down the pipe and leak through to the bowl. The refill valve then tops off the tank, causing a continuous cycle of drain and fill.
- Detect leaks in toilet tanks by dropping food coloring in the tank (12 drops). Do not flush the toilet for at least an hour. If the tank leaks the dye will show up in the bowl.
- Fill bathtubs no more than half full.

Water Efficiency Practices in the Kitchen

The following water efficiency practices can be applied to routine kitchen chores.

- Operate dishwashers with full loads only. Use the water-save cycle if your dishwasher is equipped with one.
- If washing dishes by hand, rinse them in a basin rather than under running water.
- Store drinking water in the refrigerator rather than running the tap for cold water.
- Compost food scraps rather than using a garbage disposal. Not only do disposal units waste water; the fine particles they produce can clog a septic system.
- Consider installing an instant water heater on the kitchen faucet. This reduces the time needed to run water until it becomes hot.
- Do not run water to melt ice or thaw frozen foods. Defrost them in a microwave or in the refrigerator overnight.
- Rinse vegetables in a pan of water rather than under running water.

Water Efficiency Practices in the Laundry

The laundry is usually the second highest domestic indoor water use. The following water efficiency practices are designed to save water in the laundry.

- Wash full loads only. If unable to wash a full load, set your washer to the appropriate water level setting.
- Consider replacing your top-loading, vertical-axis washer with a more efficient horizontal-axis washer. Most of these are front-loading, but some newer models are also top-loading. These washers rotate clothes rather than agitating them and use much less water, an average of 20 gallons per load compared to an average of 43 gallons for conventional washers. See the EPA's Energy Star website listed at the end of this document for a catalog of Energy Star-approved washing machines.

For Additional Information

Please contact the Drinking Water and Groundwater Bureau at (603) 271-2513 or dwgbinfo@des.nh.gov or visit our website at <http://des.nh.gov/organization/divisions/water/dwgb/index.htm>. All of the bureau's fact sheets are on-line at <http://des.nh.gov/organization/commissioner/pip/factsheets/dwgb/index.htm>. More information about the DES Water Conservation Program can be found at http://des.nh.gov/organization/divisions/water/dwgb/water_conservation/index.htm.

Resources

Woodinville, WA Water District. In-depth water-saving tips, how to check for leaks. <http://www.woodinvillewater.com/Conservation/District%20Program/District%20Program.htm>

US EPA. Listing of Energy Star rated washing machines. www.energystar.gov

References:

New England Interstate Water Pollution Control Commission (NEIWPC) *MRI Water Conservation Technical Bulletin #5, Water Conservation Best Management Practices for Domestic/Sanitary Water Use*; NEIWPC, Lowell, Mass.; 1996.
US Dept. of Defense, *MIL-Handbook-1165, Water Conservation*; US Dept. of Defense; 1997; pp 25-37.
Vickers, Amy; *Handbook of Water Use and Conservation*; WaterPlow Press, Amherst, Mass.; 2001; pp 23-75, 87-133.

Note: This fact sheet is accurate as of May 2010. Statutory or regulatory changes or the availability of additional information after this date may render this information inaccurate or incomplete.

ENVIRONMENTAL Fact Sheet



29 Hazen Drive, Concord, New Hampshire 03301 • (603) 271-3503 • www.des.nh.gov

WD-DWGB-26-3

2010

Water Efficiency Practices for Outdoor Water Use

Outdoor water uses increase water consumption during spring and summer by an average of 50 percent. Landscape watering and car washing are the two main outdoor water uses responsible for this demand for water. This increase in demand comes at a time of year when there is less water naturally available in the environment due to warmer temperatures and plant uptake.

By implementing just a few minor changes in how you use water outdoors, you will find that you can maintain your existing outdoor activities using much less water. This will save money on your water and electric bill, and protect the environment by leaving more water for New Hampshire's rivers, wetlands and aquifers. In the case of outdoor lawn watering, using water more efficiently will actually improve the durability of your grass, reduce the need for chemical amendments, and decrease lawn mowing frequency.

The following sections address conservation for landscape and garden irrigation and other outdoor uses.

Landscape and Garden Irrigation Conservation:

Use water-wise and region-appropriate landscape plantings. Visit the fact sheets webpage at www.des.nh.gov/organization/commissioner/pip/factsheets/dwgb/index.htm and scroll to WD-DWGB-26-4, "Fundamentals of Xeriscaping and Water-Wise Landscaping."

Watering frequency should be based on soil moisture, weekly precipitation and plant/turf conditions. Typically, established landscape plants and turf grass require one inch of water per week, and this amount may be applied in one application. You may see golf courses watering lush greens almost continuously; however, these are often exotic grasses that must be cooled from the heat of the day. Do not copy the watering practices of these types of operations.

Use a rain gauge to calculate your lawn and garden water needs. A rain gauge allows you to measure how much rain has fallen. These devices are available for a minimal cost at your local garden/hardware store and are easy to use. Mature lawns only require about one inch of water a week. The amount of water you should apply to your garden or lawn equals one inch minus the amount of rain you received for the week.

Soil moisture sensors are useful in determining how wet your soil is. You can check the moisture of the soil to determine watering needs. In some instances you will find that you do not need to water even if it has not rained recently.

Water only those areas that are dry. Water by hand, if possible.

Determine sprinkler or hose application volumes by placing cans at various locations in the lawn or garden. Mark a one-inch depth on the inside of the cans. Time how long it takes your sprinkler heads or hose to deliver an inch of water to each of the cans, and average the times it takes to fill each can one inch

deep. This is how long you should run your sprinklers or hose to deliver an inch of water.

Completely wet the plant root zone each time you water to prevent dry layer formations that inhibit root growth. Probe the soil after irrigating to determine whether the water reached the root zone. If water penetration is too deep, too shallow, or spotty, adjust your watering practices to correct it.

Do not over-water your lawn. Only water to the depth of the root zone. Excess water percolates too deeply, making it unavailable for plant use. Also, too much water prevents air from reaching root systems and encourages shallow roots and plant diseases.

Plant drought-resistant turf grass. The most drought-tolerant grasses are the fine leaf fescues. The University of New Hampshire Cooperative Extension recommends a mix containing hard fescue, Chewings fescue and perennial ryegrass. Most garden centers carry this type of mix.

Set your mower height to two inches. Longer grass blades retain moisture better, shade the root system, and encourage roots to grow deeper and stronger.

Keep the mower blades sharp. Mowing with a dull blade gives grass a "split ends" look making it seem drier than it is.

Give lawns the lowest priority for watering, since they are able to go dormant for long periods of time, slower to die and less expensive to replace than other vegetation.

If using a sprinkler system, connect it to an automatic timer. If you do not have a timed system, set a kitchen timer to avoid over-watering.

Be sure sprinkler heads are producing drops rather than a mist. This helps to reduce evaporation.

If you use automatic, pop-up sprinkler heads, choose the type that incorporate electronic sensors to monitor soil moisture and rain events. Periodically check to ensure sensors are operating properly.

Operate automatic sprinkler systems connected to public water systems only when the water demand is low, usually between 4 a.m. and 6 a.m.

Irrigate between 9 p.m. and 9 a.m. to prevent evaporative water loss.

Don't water the pavement. Adjust sprinklers so that they water only the plants.

For larger systems, develop an irrigation maintenance program. Routinely inspect all water lines, valves and pumps for leaks. Keep replacement and repair parts on hand. Inspect sprinkler nozzles to ensure they are operating properly and are distributing the water uniformly. Evaluate irrigation system pressures to better control application rates.

Apply appropriate fertilizers to encourage the growth you want in your plants. Nitrogen promotes leaf growth, phosphorus benefits fruits and flowers and potassium promotes root development. For instance, lettuces require primarily nitrogen; grass needs nitrogen in the spring and potassium the rest of the growing season. Roses and tomatoes call for phosphorus. Usually a balanced fertilizer, such as 10-10-10 that contains 10 percent each of potassium, phosphorus and nitrogen, is best for vegetables, shrubs and flowers. Specialty fertilizers for lawns contain higher percentages of either nitrogen or potassium depending upon what time of year they should be applied.

Do not irrigate during windy conditions.

Utilize drip or trickle irrigation wherever possible. These systems apply water near the root zone of the plant, ensuring a complete watering while lessening excess water usage.

Plant species native to New Hampshire. Native plants are hardier and tend to need less water. Visit the New England Wildflower Society's website at www.newfs.org for information about native plants.

Use mulch to retain moisture. Mulch can be used almost everywhere in the garden, even on row vegetables. Mulch hay, straw and sheet composting work well in the vegetable garden.

Minimize your lawn area. Replace grass with moss, rocks, gravel, wood chips or mulched flowerbeds. Consider xeriscape or "Zen" gardens. Xeriscape effectively uses drought-tolerant vegetation that subsists on precipitation alone. Zen gardens traditionally contain no vegetation, only raked sand, sculpture and a water feature. See fact sheet WD-DWGB-26-4 "[Fundamentals of Xeriscape and Water-Wise Landscaping](#)" for more information.

Use rain barrels, cisterns, and ponds to collect water that can be reused for gardens.

Establishing Turf grass:

Underlay turf areas with at least six inches of loam.

Choose a drought-resistant seed mix that favors at least 50 percent fine leaved fescues. You will need three to four pounds of seed per 1,000 square feet. Try to avoid mixes that contain Kentucky bluegrass. This grass, despite its name, is actually a native to England and requires a whopping 35 inches of rain a growing season to survive.

Test your soil. Fine leaf fescues thrive at pH values between 5 and 6.5. If your soil test indicates more acid conditions apply lime at a rate of 50 lbs/1,000 square feet. Contact your county cooperative extension for cost and information on obtaining a soil test kit. See extension.unh.edu for a complete listing of UNH county extension services and contacts.

Apply a starter-type fertilizer and till lime and fertilizer into the top 6 inches of the soil.

Rake and smooth the soil.

Apply seed uniformly. A broadcast spreader is an excellent tool for seeding lawns. The two most common types of spreaders are push spreaders that drop the seed out of the bottom of a hopper as you walk behind them and the crank type that broadcast the seed in a circular pattern from the hopper as you turn a crank. Make sure you overlap your passes with the seeder to avoid bare spots.

Roll or tamp the soil to make sure you have good seed-to-soil contact. The seed must be in contact with the soil to germinate. Water the area thoroughly.

Apply a weed-free mulch such as straw. Don't allow the seeded area to dry out, as seeds also need moisture to germinate.

The best time to plant grass seed in New Hampshire is August through September. If you plant earlier there is greater risk of broadleaf weed infestation. If you plant too late in the season the slow-germinating fescues will not have time to establish a good root system before freeze-up. Once established, a lawn of fine leaved fescues requires no watering. For more information, visit the UNH Cooperative Extension's website at extension.unh.edu.

Other Outdoor Water Use Conservation:

Cover swimming pools when not in use to prevent evaporation.

Lower the water level in the pool to prevent water loss from splashing.

Minimize pool filter backwashing.

Wash vehicles using a bucket and sponge, using a hose for rinsing only.

Sweep driveways, walks and decks with a broom rather than hosing them off.

Use hose nozzle shutoff devices.

Check your irrigation system, outdoor faucets, and hose connections for leaks. A 25-cent hose gasket can save money on your water or electric bill.

For Additional Information

Please contact the Drinking Water and Groundwater Bureau at (603) 271-2513 or dwgbinfo@des.nh.gov or visit our website at <http://des.nh.gov/organization/divisions/water/dwgb/index.htm>. All of the bureau's fact sheets are on-line at <http://des.nh.gov/organization/commissioner/pip/factsheets/dwgb/index.htm>. More information about the DES Water Conservation Program can be found at http://des.nh.gov/organization/divisions/water/dwgb/water_conservation/index.htm

Additional Resources

University of NH Cooperative Extension, Home & Garden Education Program. Phone: 1-877-398-4769

UNH Cooperative Extension. Links to home and garden fact sheets.
www.extension.unh.edu/resources/category/Home_and_Garden

North Carolina Cooperative Extension. Detailed fact sheet on efficient irrigation. Includes directions for setting up a drip irrigation or sprinkler system.
www.bae.ncsu.edu/programs/extension/publicat/wqwm/ag508_6.html

References

_____; *MRI Water Conservation Technical Bulletin #7, Water Conservation Best Management Practices for Landscape and Turf Management*; New England Interstate Water Pollution Control Commission, Wilmington, MA; 1996.

_____; *MIL-Handbook-1165, Water Conservation*; US Dept. of Defense; 1997; pp 67-75.

Vickers, Amy; *Handbook of Water Use and Conservation*; WaterPlow Press, Amherst, MA; 2001; pp 140-223.