

Wetlands Applications Decision Report

Decisions Taken

9/7/2020 to 9/13/2020

DISCLAIMER:

This document is published for information purposes only and does not constitute an authorization to conduct work. Work in jurisdiction may not commence until the applicant has received a posting permit.

Decisions are subject to appeal, and are reviewed by the federal agencies for compliance with Section 404 of the Federal Clean Water Act.

APPEAL:

Any party aggrieved by a decision may file an appeal within 30 days of the date of this decision as specified in RSA 482-A:10, RSA 21-O:14, and the rules adopted by the Wetlands Council, Env-WtC 100-200.

The appeal must be filed directly with the Council, c/o the Council Appeals Clerk, who may be contacted at (603) 271-6072 or at appeals@des.nh.gov. The notice of appeal must set forth fully every ground upon which it is claimed that the decision complained of is unlawful or unreasonable. Only those grounds set forth in the notice of appeal can be considered by the council.

PERMIT TYPE: STANDARD DREDGE AND FILL APPLICATION

PERMIT CATEGORY: MAJOR IMPACT PROJECT

2017-01302

OWNER: NH DEPT OF TRANSPORTATION

TOWN: WALPOLE

WATERBODY: CONNECTICUT RIVER

Related Parties

Name: TOWN OF CHARLESTOWN
Address: PO BOX 385
Phone: 6038264400
Fax/Email: FAX - 603-826-5181

Name: JOHN BRUNO
Address: PO BOX 1273
Phone: 6034452307
Fax/Email:

AGENT

Name: JACOBS ENGINEERING GROUP
Address: TWO EXECUTIVE PARK DR
Phone: 6036667181
Fax/Email: CLINTON.MERCER@JACOBS.COM

LAC

Name: CONNECTICUT RIVER MT ASCUTNEY LAC
Address: 10 WATER ST SUITE 225
Phone:
Fax/Email:

LAC

Name: CONNECTICUT RIVER WANTASTIQUET LAC
Address: 10 WATER ST STE 225
Phone: 6034481680
Fax/Email:

OWNER

Name: NH DEPT OF TRANSPORTATION
Address: PO BOX 483
Phone: 6032712171
Fax/Email:

Requested Action:

Request to amend permit to read:

Reconstruct and widen approximately 2.7 miles of NH 12 from Main St. in Walpole to Route 12A in Charlestown upgrading drainage and stormwater management along with utility relocation and guardrail installation impacting 429,854 sq. ft. (101,405 sq. ft. temporary) of riverine and palustrine wetlands.

Compensatory mitigation includes a total payment of \$1,318,873.52 to the Aquatic Resource Mitigation Fund. NHDOT project #14747.

Conservation Commission / Staff Comments:

LAC submitted concerns

Cons. Comms. - no comments

APPROVE AMENDMENT

Amend permit to read:

Reconstruct and widen approximately 2.7 miles of NH 12 from Main St. in Walpole to Route 12A in Charlestown upgrading drainage and stormwater management along with utility relocation and guardrail installation impacting 429,854 sq. ft. (101,405 sq. ft. temporary) of riverine and palustrine wetlands. Compensatory mitigation includes a total payment of \$1,318,873.52 to the Aquatic Resource Mitigation Fund. NHDOT project #14747.

With Conditions:

1. All work shall be in accordance with:

- a. Plans by NHDOT Bureau of Highway Design dated 5/4/2017 as received by the Department on May 9, 2017
- b. Plans by NHDOT Bureau of Highway Design dated 08-2017 as received by the Department on Aug. 28, 2017 and
- c. Plans by NHDOT Bureau of Highway Design (sheets 8-10 and 13-16 of 29) Amended Dec. 2017 as received by the Department on Jan. 10, 2018 and
- d. Revised plans by NHDOT Bureau of Highway Design (sheets 16 of 29 and Cross-Section 1 of 1) Amended Aug. 2020 as received by the Department on Aug. 31, 2020.

2. At least 48 hours prior to the start of construction, a pre-construction meeting shall be held with NHDES Land Resources Management Program staff at the project site, at the NHDES Office in Concord, N.H. or NHDOT Office in Concord, N.H. to review the conditions of this wetlands permit.

3. It shall be the responsibility of the permittee to schedule and coordinate the pre-construction meeting providing at least 5-day notice to the NHDES Wetlands Bureau and / or other Land Resources Management Program staff, and the meeting shall be attended by the permittee, the contract administrator(s), wetlands scientist(s), erosion control monitor, and the contractor(s) responsible for performing the work.

4. Any dredged material shall be placed out of the DES Wetlands Bureau jurisdiction unless specifically authorized.

5. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and shall remain until the area is stabilized.

6. Construction equipment shall not be located within surface waters.

7. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, with a preferred undisturbed vegetated buffer of at least 50 feet and a

minimum undisturbed vegetative buffer of 20 feet.

8. Within three days of the last activity in an area, all exposed soil areas, where construction activities are complete, shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack on slopes steeper than 3:1 or netting /matting and pinning on slopes steeper than 2:1.

9. Where construction activities have been temporarily suspended within the growing season, all exposed soil areas shall be stabilized within 14 days by seeding and mulching or if temporarily suspended outside the growing season, all exposed areas shall be stabilized within 14 days by mulching, mulching with tack on slopes steeper than 3:1 and stabilized by matting and pinning on slopes steeper than 2:1.

10. The contractor responsible for completion of the work shall utilize techniques described in the New Hampshire Stormwater Manual, Volume 3, Erosion and Sediment Controls During Construction (December 2008).

11. Extreme precautions to be taken within riparian areas to limit unnecessary removal of vegetation during road construction and areas cleared of vegetation to be revegetated as quickly as possible.

12. The retention of mature trees whether alive or dead shall occur along the river edge wherever possible to maintain the opportunity for eagle perches.

13. There shall be no further alteration to wetlands or surface waters without amendment of this permit.

14. Proper headwalls shall be constructed within seven days of culvert installation.

15. Work shall be done during low flow.

16. Should invasive species be encountered during construction, the contractor will follow the appropriate procedures outlined in NHDOT's Best Management Practices for Roadside Invasive Plants, dated 2008 to ensure proper handling and disposal.

17. This permit is contingent on the issuance of and compliance with the Section 401 Water Quality certification.

18. Mitigation Project Monitoring plan to be submitted prior to construction in accordance with Env-Wt 803.04.

19. In accordance Env-Wt 803.04 plantings shall be monitored for no fewer than 5 growing seasons.

20. The mitigation areas shall have at least 75% successful establishment of vegetation after two (2) growing seasons, or shall be replanted and re-established until a functional and stable embankment is replicated in a manner satisfactory to the DES Wetlands Bureau.

21. A post-construction report documenting the status of the completed project with photographs shall be submitted to the Wetlands Bureau within 60 days of the completion of construction.

22. A copy of the final plan set is to be made available to the public via the NHDOT website.

With Findings:

1. This is a major impact project per Administrative Rule Env-Wt 303.02(c) and (i) alteration of more than 20,000 sq. ft. of non-tidal wetlands and more that 200 linear feet of impacts to streams and banks.

2. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.

3. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.

4. The request for an amended permit was received on January 10, 2018 to avoid an archeologically sensitive area and provide continued driveway access in one location.

5. An additional request for amended permit was received on August 31, 2020. While preparing to

replace the 66-inch RCP in-kind and constructing a new outlet headwall the contractor identified that the soils were not suitable to support the installation of a new headwall resulting in a necessary design change. All of the work is proposed within the previously permitted impact area. The design change is referenced in the amendment plans.

6. The project engineer has confirmed the scour potential at the outlet pipe to be low and the revised outlet apron will provide the same BMP benefit.

Mitigation:

7. The applicant has reviewed on-site options for mitigation and the department has determined that a portion of this project that is not being mitigated is acceptable for payment to the Aquatic Resource Mitigation (ARM) Fund to compensate for the wetland areas not previously impacted by the existing roadway.

8. Compensatory mitigation included a total payment of \$1,318,873.52 to the Aquatic Resource Mitigation Fund.

9. Compensatory mitigation for the additional amended wetland loss resulting from the 2017 amended permit request equals \$13,252.07.

10. The payment calculated for the proposed wetland loss resulting from the previous permit request was received by DES Wetlands Bureau on February 1, 2018. No additional compensatory is required since there are no proposed changes to impact areas associated with the amendment.

11. The Department decision is issued in letter form and upon receipt of the ARM fund payment for the amended impacts, the Department shall issue an amended posting permit in accordance with Env-Wt 803.08(f).

PERMIT TYPE: STANDARD DREDGE AND FILL APPLICATION

PERMIT CATEGORY: MAJOR IMPACT PROJECT

2019-03695

OWNER: TOWN OF STODDARD

TOWN: STODDARD

WATERBODY: KENNEDY BROOK

Related Parties

AGENT

Name: DUBOIS & KINGS INC
Address: 18 CONSTITUTION DR STE 8
Phone: 6036371043
Fax/Email: DCARTER@DUBOIOUS-KING.COM

OWNER

Name: TOWN OF STODDARD
Address: 1450 RTE 123 NORTH
Phone: 6034463326
Fax/Email: STODDARDTOWNHALL@MYFAIRPOINT.NET

Requested Action:

Temporarily impact 489 square feet (SF) within the bed and banks of Kennedy Brook (tier 3, impacting 72 linear feet) to replace twin 4.5 foot diameter by 50.6 foot long culverts with a 25 foot span by 6 foot high by 28 foot long open-bottom bridge, and for access, installation, and erosion, sediment, and turbidity controls. Restore 482 SF (79 linear feet) of Kennedy Brook channel bed and bank at the inlet and outlet.

NA

APPROVE PERMIT

Temporarily impact 489 square feet (SF) within the bed and banks of Kennedy Brook (tier 3, impacting 72 linear feet) to replace twin 4.5 foot diameter by 50.6 foot long culverts with a 25 foot span by 6 foot high by 28 foot long open-bottom bridge, and for access, installation, and erosion, sediment, and turbidity controls. Restore 482 SF (79 linear feet) of Kennedy Brook channel bed and bank at the inlet and outlet.

With Conditions:

1. All work shall be in accordance with revised plans dated September 10, 2020, by DuBois & King, Inc., as received by the NH Department of Environmental Services (NHDES) on September 11, 2020.
2. This permit is contingent on review and approval, by the NHDES Wetlands Bureau, of final stream diversion and erosion control plans. Those plans shall detail the relative timing and method of stream flow diversion during construction, and show temporary siltation, erosion, and turbidity control measures to be implemented.
3. Not less than 5 state business days prior to starting work authorized by this permit, the permittee shall notify the NHDES Wetlands Bureau and the local conservation commission in writing of the date on which work under this permit is expected to start.
4. A post-construction report, prepared by a Certified Wetland Scientist or Qualified Professional, as applicable, documenting status of the project area and restored jurisdictional area, including photographs, shall be submitted to the NHDES Wetlands Program within 60 days of the completion of construction. The NHDES Wetlands Program may require subsequent monitoring and corrective measures

if NHDES deemed the area inadequately stabilized or restored.

5. Any further alteration of areas on this property that are subject to RSA 482-A jurisdiction will require a new application and further permitting.
6. No person undertaking any activity shall cause or contribute to, or allow the activity to cause or contribute to, any violations of the surface water quality standards in RSA 485-A and Env-Wq 1700.
7. The contractor responsible for completion of the work shall use techniques described in the New Hampshire Stormwater Manual, Volume 3, Erosion and Sediment Controls During Construction (December 2008).
8. Appropriate siltation and erosion controls shall be in place prior to construction, shall be maintained during construction, and shall remain until the area is stabilized. Temporary controls shall be removed once the area has been stabilized.
9. Erosion control products shall be installed per manufacturers recommended specifications.
10. Work shall be conducted in a manner so as to minimize turbidity and sedimentation to surface waters and wetlands.
11. No excavation shall be done in flowing water. No construction equipment shall be operated in flowing water.
12. Prior to commencing work on a substructure located within surface waters, the permittee or permittee's contractors shall construct a cofferdam to isolate the substructure work area from the surface waters.
13. Work within the stream, inclusive of work associated with installation of a cofferdam, shall be done during periods of low flow only. The permittee shall monitor local weather forecasts to avoid working during or following precipitation events. Once the cofferdam is fully effective, confined work can proceed without restriction.
14. The temporary cofferdam shall be entirely removed within 2 days after work within the cofferdam is completed and water has returned to normal clarity.
15. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, with a preferred undisturbed vegetated buffer of at least 50 feet and a minimum undisturbed vegetative buffer of 20 feet.
16. Dredged materials, whether to be stockpiled or disposed of, shall be dewatered in sedimentation basins lined with siltation and erosion controls, and located outside of areas subject to RSA 482-A jurisdiction.
17. Construction equipment shall be inspected daily for leaking fuel, oil, and hydraulic fluid prior to entering surface waters or wetlands or operating in an area where such fluids could reach groundwater, surface waters, or wetlands.
18. The permittee's contractor shall maintain appropriate oil/diesel fuel spill kits on site that are readily accessible at all times during construction, and shall train each operator in the use of the kits.
19. All refueling of equipment shall occur outside of surface waters or wetlands during construction. Machinery shall be staged and refueled in upland areas only.
20. Faulty equipment shall be repaired immediately prior to entering areas that are subject to RSA 482-A jurisdiction.
21. Native material removed from the streambed during bridge installation shall be stockpiled separately and reused to emulate a natural channel bottom through the crossing, between wing walls, and beyond. Any new materials used must be as similar to the natural stream substrate as practicable and shall not include any angular rock.
22. Materials used to emulate a natural channel bottom must be consistent with the streambed materials

identified in the reference reach, and shall not include angular riprap or gravel unless specifically identified on the approved plans.

23. Any fill used shall be clean sand, gravel, rock, or other suitable material.

24. Area of temporary impact shall be regraded to original contours following completion of work.

25. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tackifiers on slopes less than 3:1 or netting and pinning on slopes steeper than 3:1.

With Findings:

1. This project is classified as a Major Project per NH Administrative Rule Env-Wt 303.02(p), for replacement of a stream crossing which meets the criteria for a tier 3 stream crossing as specified in Env-Wt 904.04(a).
2. The proposed project is a tier 3 stream crossing replacement as it is located on a watercourse with a contributing watershed size of 640 acres or greater, per Rule Env-Wt 904.04(a)(1), and it is within the 100 year floodplain, per Rule Env-Wt 904.04(a)(4).
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03. Replacement of the existing tier 3 stream crossing is unavoidable, as it is severely deteriorated. All impacts are temporary, and restoration will occur within the stream channel bed and banks as the permitted structure length is 22.6 feet less than the existing structure length.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(a), Requirements for Application Evaluation, has been considered in the design of the project.
5. The agent has provided a technical report requesting that the crossing be considered an Alternative Design per NH Administrative Rule Env-Wt 904.09(b), as the proposed entrenchment ratio (ER) through the crossing does not meet the minimum ER of the stream type in accordance with the NH Stream Crossing Guidelines. Within the report, the agent has demonstrated that the proposed crossing meets the general design criteria specified in Env-Wt 904.01, and the specific design criteria specified in Env-Wt 904.05 to the maximum extent practicable. Therefore, the applicant has met all of the requirements for a tier 3 stream crossing alternative design, per Env-Wt 904.09(c).
6. In accordance with NH Administrative Rule Env-Wt 904.04(f), compensatory mitigation shall not be required as this project is considered self-mitigating for the following reasons: the proposed structure will pass the flows of a modeled 100-yr storm event; the proposed structure is open-bottom and the natural stream channel will be restored through the crossing.
7. Under existing conditions, the modeled 100-yr flood elevation at the inlet is 1,530.3 feet. Under proposed conditions, the modeled 100-yr flood elevation at the inlet is 1,527.9 feet.
8. Under existing conditions, the modeled flow velocity at the outlet is 11.9 fps. Under proposed conditions, the modeled flow velocity is 6.1 fps.
9. No comments of concern have been received by NHDES from abutters.
10. Based on the plans, no portion of the work will fall outside of the existing Right-of-Way.
11. The New Hampshire Natural Heritage Bureau (NHB) has reviewed the proposed project (NHB19-3324) and has determined that there are no recorded occurrences of sensitive species near the project area, per the letter dated October 15, 2019.
12. The Stoddard Conservation Commission has not provided comments to NHDES regarding this

Wetland Application.

13. The applicant requested a Commissioner's Expedited review of the stream crossing in need of replacement, as it is located under a road that provides a single point of egress to 250 Stoddard homes and because the NH Department of Transportation has weight rated the road as not passable for vehicles over ten tons, including emergency vehicles and school buses.

14. An emailed request for a Commissioner's Expedited review and application materials, in accordance with Rule Env-C 209.07, were received on August 31, 2020. Hard copies were received on September 2, 2020, and on September 3, 2020 the Commissioner's Expedited request was approved because the application had met the criteria set forth in Env-C 209.07, whereby an expedited review is "necessary to abate a substantial and imminent threat to public health or safety".

15. In accordance with RSA 482-A:8, NHDES finds that the requirements for a public hearing do not apply as the permitted project is not of substantial public interest, and will not have a significant impact on or adversely affect the values of the riverine resource, as identified under RSA 482-A:1.

PERMIT TYPE: STANDARD DREDGE AND FILL APPLICATION

PERMIT CATEGORY: MAJOR IMPACT PROJECT

2020-00412

OWNER: TOWN OF WENTWORTH

TOWN: WENTWORTH

WATERBODY: NA

Related Parties

AGENT

Name: HEB ENGINEERS INC
Address: PO BOX 440
Phone: 6033566936
Fax/Email:

OWNER

Name: TOWN OF WENTWORTH
Address: PO BOX 2
Phone: 6037649955
Fax/Email: TOWNOFWENTWORTH@WENTWORTH-NH.ORG

Requested Action:

Retain approximately 698 square feet (118 linear feet) of dredge and fill within the bed and banks of Rocky Pond Brook (Tier 3) for the replacement of the existing 16 foot wide, 20 foot long span bridge with two, 20 foot long 7 foot diameter culverts. Temporary impacts consist of 323 square feet within palustrine forested wetlands and 636 square feet (94 linear feet) within the bed and banks of the stream.

NA

DENY PERMIT-INSUFFICIENT & UNTIMELY RESP

Retain approximately 698 square feet (118 linear feet) of dredge and fill within the bed and banks of Rocky Pond Brook (Tier 3) for the replacement of the existing 16 foot wide, 20 foot long span bridge with two, 20 foot long 7 foot diameter culverts. Temporary impacts consist of 323 square feet within palustrine forested wetlands and 636 square feet (94 linear feet) within the bed and banks of the stream.

PERMIT TYPE: STANDARD DREDGE AND FILL APPLICATION

PERMIT CATEGORY: MINIMUM IMPACT PROJECT

2020-01769

OWNER: CONSTANCE/RICHARD QUINDLEY

TOWN: ALTON

WATERBODY: MANMADE POND

Related Parties

AGENT

Name: STONEY RIDGE ENVIRONMENTAL LLC
Address: 229 PROSPECT MOUNTAIN RD
Phone: 6037765825
Fax/Email:

APPLICANT

Name: TOWN OF ALTON HIGHWAY DEPT
Address: PO BOX 659
Phone: 6038756808
Fax/Email: 603-875-6809

OWNER

Name: CONSTANCE/RICHARD QUINDLEY
Address: 321 HALLS HILL RD
Phone:
Fax/Email:

Requested Action:

Dredge 2,144 square feet of palustrine emergent wetland in order to maintain an existing active man-made pond used as a sediment retention basin by removing built-up sediment and overgrowth that is causing pond overflow.

NA

APPROVE PERMIT

Dredge 2,144 square feet of palustrine emergent wetland in order to maintain an existing active man-made pond used as a sediment retention basin by removing built-up sediment and overgrowth that is causing pond overflow.

With Conditions:

1. In accordance with Env-Wt 307.16, all work shall be done in accordance with the approved plans dated June 19, 2020 by Stoney Ridge Environmental, LLC, as received by the NH Department of Environmental Services (NHDES) on July 23, 2020.
2. In accordance with Env-Wt 310.03(a), no other work shall be done on the subject property pursuant to another expedited permit (EXP) or a statutory permit-by-notification (SPN) for a period of 12 months from the date the EXP was issued unless the property owner submits information, including a plan, to demonstrate that the proposed work is wholly unrelated to and separate from the work already done under the EXP or SPN; and the proposed work and the work already done under the EXP or SPN do not,

when combined, constitute a project for which a standard permit is required.

3. In accordance with Env-Wt 310.03(c), any work shall be timed and carried out to protect documented occurrences of cold water or threatened or endangered fisheries.

4. In accordance with Env-Wt 310.03(b), the work shall comply with all applicable conditions specified in Env-Wt 307.

5. In accordance with Env-Wt 307.10(a), no dredging shall occur that would create violations of any set-backs specified in RSA 485-A or 483-B relative to protecting water quality; or Env-Wq 1000 relative to septic systems.

6. In accordance with Env-Wt 307.03(a), no activity shall be conducted in such a way as to cause or contribute to any violation of surface water quality standards specified in RSA 485-A:8 or Env-Wq 1700; ambient groundwater quality standards established under RSA 485-C; limitations on activities in a sanitary protective area established under Env-Dw 302.10 or Env-Dw 305.10; or any provision of RSA 485-A, Env-Wq 1000, RSA 483-B, or Env-Wq 1400 that protects water quality.

7. In accordance with Env-Wt 307.03(b), all work, including management of soil stockpiles, shall be conducted so as to minimize erosion, minimize sediment transfer to surface waters or wetlands, and minimize turbidity in surface waters and wetlands using the techniques described in Env-Wq 1505.02, Env-Wq 1505.04, Env-Wq 1506, and Env-Wq 1508; the applicable BMP manual; or a combination thereof, if the BMP manual provides less protection to jurisdictional areas than the provisions of Env-Wq 1500.

8. In accordance with Env-Wt 307.10(b), work shall be done during low flow or in the dry unless a dredge dewatering, diversion, or cofferdam plan has been approved as part of the project.

9. In accordance with Env-Wt 307.03(c)(3), water quality control measures shall be installed prior to start of work and in accordance with the manufacturer's recommended specifications or, if none, the applicable requirements of Env-Wq 1506 or Env-Wq 1508.

10. In accordance with Env-Wt 307.03(c)(5), water quality control measures shall be maintained so as to ensure continued effectiveness in minimizing erosion and retaining sediment on-site during and after construction.

11. In accordance with Env-Wt 307.03(f)(1), a cofferdam or other turbidity control shall be used to enclose a dredging project conducted in or along the shoreline of a bog, marsh, lake, pond, stream, river, creek, or any other surface water, provided that a coffer dam shall not be installed during periods of high flow.

12. In accordance with Env-Wt 307.10(c), turbidity controls shall be installed prior to construction and maintained during construction such that no turbidity escapes the immediate dredge area; and remain in place until suspended particles have settled and water at the work site has returned to normal clarity.

13. In accordance with Env-Wt 307.03(f)(2), a coffer dam or other turbidity control shall be removed after work within the coffer dam or other turbidity control is completed, the contained water has returned to background clarity, and when removing the structure will not cause or contribute to a violation of Env-Wt 307.03(c)(6).

14. In accordance with Env-Wt 519.07(c), discharges from dewatering shall be to sediment basins that are located in upland areas at least 20 feet from any waterbody; and lined with hay bales or other sediment-trapping liners.

15. In accordance with Env-Wt 307.10(d), dredged materials shall be disposed of out of jurisdictional areas, unless other disposition is specifically permitted pursuant to Env-Wt 307.10(e).

16. In accordance with Env-Wt 307.10(l), dredging shall not disturb contaminated sediment unless dredging of such sediment is specifically identified in the application, and implemented with such protective conditions as are necessary to ensure that the contaminated sediment is properly managed.

17. In accordance with Env-Wt 307.15(a), heavy equipment shall not be operated in any jurisdictional area unless specifically authorized by this permit.

18. In accordance with Env-Wt 307.03(h), equipment shall be staged and refueled outside of jurisdictional areas (unless allowed) and in accordance with Env-Wt 307.15.
19. In accordance with Env-Wt 307.05(b), equipment to be used in surface waters shall be completely free of all aquatic and terrestrial invasive plants and all exotic aquatic species of wildlife as defined in RSA 487:16, I-a.
20. In accordance with Env-Wt 307.05(e), to prevent the use of soil or seed stock containing nuisance or invasive species, the contractor responsible for work shall follow Best Management Practices for the Control of Invasive and Noxious Plant Species (Invasive Plant BMPs).
21. In accordance with Env-Wt 307.12(a), within 3 days of final grading or temporary suspension of work in an area that is in or adjacent to surface waters, all exposed soil areas shall be stabilized by seeding and mulching, if during the growing season; or mulching with tackifiers on slopes less than 3:1 or netting and pinning on slopes steeper than 3:1 if not within the growing season.

With Findings:

1. This is classified as a minimum impact project per Rule Env-Wt 519.09(a), as the project meets all of the criteria to maintain a constructed pond.
2. Per Rule Env-Wt 310.01(d)(4), the applicant provided a signed statement certifying that the proposal is the alternative with the least adverse impact to jurisdictional areas, as required by Env-Wt 313.03.
3. Per Rule Env-Wt 310.01(h), the application for this expedited permit (EXP) included a signed statement from the municipal conservation commission certifying that the conservation commission waives its right to intervene on the project.
4. Per Rule Env-Wt 306.05, the applicant has addressed all of the required planning items that are used to determine the appropriate impact classification of a project and the type of approval required.
5. This dredging project meets the approval criteria established in Env-Wt 523.02(b), as it is part of a previously-constructed maintenance dredge project that is not abandoned or an active man-made pond.
6. Per Rule Env-Wt 313.01(a)(5) and pursuant to RSA 482-A:11, II, the applicant obtained written consent from abutting landowner(s) as a portion of the proposed project will extend onto another property, to ensure that the project does not infringe on the property rights or unreasonably affect the value or enjoyment of the property of abutting owners.
7. Per Rule Env-Wt 202.01(b) and as required by RSA 482-A:8, NHDES finds that the requirements for a public hearing do not apply as the project will not have a significant environmental impact, as defined in Env-Wt 104.19, on the resources protected by RSA 482-A, or, is not of substantial public interest, as defined in Env-Wt 104.32.
8. Per Rule Env-Wt 202.01(a), the department finds the project is clearly defined, therefore no hearing is required, as contemplated by RSA 482-A:3, XIV(a)(3)(C) or RSA 482-A:3, XIV(a)(4)(C).

PERMIT TYPE: EXPEDITED MINIMUM

PERMIT CATEGORY: MINIMUM IMPACT PROJECT

2020-01643

OWNER: LARRY ROBBINS

TOWN: SPOFFORD

WATERBODY: SPOFFORD LAKE

Related Parties

OWNER

Name: LARRY ROBBINS
Address: 18 NAMASCHAUG LANDING
Phone: 4139496970
Fax/Email: LROBBINS@MASSMED.ORG

Requested Action:

Install a seasonal boatlift adjacent to an existing 4 foot x 30 foot pier on 108 feet of frontage along Spofford Lake in Spofford.

NA

APPROVE PERMIT

Install a seasonal boatlift adjacent to an existing 4 foot x 30 foot pier on 108 feet of frontage along Spofford Lake in Spofford.

With Conditions:

1. In accordance with Env-Wt 307.16, all work shall be done in accordance with the approved plans as received by the NH Department of Environmental Services (NHDES) on August 26, 2020.
2. This permit shall not be effective until it has been recorded in the Cheshire County Registry of Deeds and a copy of the recorded permit has been provided to the department as required pursuant to RSA 482-A:3, and Env-Wt 314.02.
3. Only those structures shown on the approved plans shall be installed or constructed along this frontage as required per Env-Wt 513.22, (a).
4. All portions of the docking structures shall be located at least 20 feet from the abutting property lines and no watercraft shall be secured to the docking facility such that it crosses over the imaginary extension of the property lines over the surface water as required by RSA 482-A:3, XIII.
5. All seasonal structures, including watercraft lifts, shall be removed for the non-boating season as required per Env-Wt 513.22.
6. Pursuant to RSA 482-A:14, RSA 482-A:14-b, and RSA 482-A:14-c, NHDES is authorized to take appropriate compliance actions should it be determined that, based upon additional information which becomes available, any of the structures depicted as "existing" on the plans submitted by or on behalf of the permittee were not previously permitted or grandfathered.

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 513.24(a)(1), installation of a lift compliant with Env-Wt 513.24(a)(1).

2. The Department finds that the project as proposed and conditioned meets the requirements of RSA 482-A and the Wetlands Program Code of Administrative Rules Chapters Env-Wt 100 - 900. No waivers of RSA 482-A or the Wetlands Program Code of Administrative Rules Chapters Env-Wt 100 - 900 were requested or approved under this permit action.

PERMIT TYPE: EXPEDITED MINIMUM

PERMIT CATEGORY: EXP - EXPEDITED TIMELINE

2020-01614

OWNER: MADGE H NICKERSON REVOCABLE TRUST

TOWN: ALTON

WATERBODY: LAKE WINNIPESAUKEE

Related Parties

AGENT

Name: STONEY RIDGE ENVIRONMENTAL LLC
Address: 233 PROSPECT MTN RD
Phone: 6037765825
Fax/Email: CBALCIUS@STONEYRIDGEENV.COM

OWNER

Name: MADGE H NICKERSON REVOCABLE TRUST
Address: 400 ROBERTS COVE RD
Phone: 6035696966
Fax/Email:

Requested Action:

Repair an existing 7.75 foot x 30 foot and 4.5 foot x 30 foot "U" shaped permanent pier and replace existing permanent dock supports on 215 feet of frontage along Lake Winnepesaukee in Alton.

NA

APPROVE PERMIT

Repair an existing 7.75 foot x 30 foot and 4.5 foot x 30 foot "U" shaped permanent pier and replace existing permanent dock supports on 215 feet of frontage along Lake Winnepesaukee in Alton.

With Conditions:

1. In accordance with Env-Wt 307.16, all work shall be done in accordance with the approved plans dated June 12, 2020 by Stoney Ridge Environmental LLC as received by the NH Department of Environmental

Services (NHDES) on July 8, 2020.

2. This permit shall not be effective until it has been recorded in the Belknap County Registry of Deeds and a copy of the recorded permit has been provided to the department as required pursuant to RSA 482-A:3, and Env-Wt 314.02.
3. Any subdivision of the property frontage will require removal of a sufficient portion of the docking structures to comply with the dock size and density requirements in effect at the time of the subdivision as required to maintain compliance with Env-Wt 314.02 and Env-Wt 513.12.
4. Only those structures shown on the approved plans shall be repaired along this frontage as required per Env-Wt 513.22, (a).
5. All portions of the docking structures shall be located at least 20 feet from the abutting property lines and no watercraft shall be secured to the docking facility such that it crosses over the imaginary extension of the property lines over the surface water as required by RSA 482-A:3, XIII.
6. Crib material shall be timber, concrete, or other non-toxic material, and of such size and spacing as necessary to completely contain the ballast as required per Env-Wt 513.15, (g), (4).
7. No agitating or heating device shall be installed for the purpose of inhibiting the formation of ice in proximity to the approved structures unless it has been registered with the municipal clerk of the town in which such device shall be operated pursuant to RSA 270:34 Registration Required.
8. Pursuant to RSA 270:33, Heating, Agitating, or Other Devices in Public Waters; Safety Hazard, no agitating or heating device installed in accordance with RSA 270:34 shall inhibit or prevent the natural formation of ice in such a manner as to impede either the ingress or egress to or from the ice from any property other than that of the owner of the device.
9. Work authorized shall be carried out in accordance with Env-Wt 307 such that appropriate turbidity controls are in place to protect water quality, that no turbidity escapes the immediate dredge area, and that appropriate turbidity controls shall remain until suspended particles have settled and water at the work site has returned to normal clarity.
10. Pursuant to RSA 482-A:14, RSA 482-A:14-b, and RSA 482-A:14-c, NHDES is authorized to take appropriate compliance actions should it be determined that, based upon additional information which becomes available, any of the structures depicted as "existing" on the plans submitted by or on behalf of the permittee were not previously permitted or grandfathered.

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 513.24(a)(2), replace a legal structure.
2. The Department finds that the project as proposed and conditioned meets the requirements of RSA 482-A and the Wetlands Program Code of Administrative Rules Chapters Env-Wt 100 - 900. No waivers of RSA 482-A or the Wetlands Program Code of Administrative Rules Chapters Env-Wt 100 - 900 were requested or approved under this permit action.

PERMIT TYPE: EXPEDITED MINIMUM

PERMIT CATEGORY:

2020-01994

OWNER: BETHEL BUILDERS LLC

TOWN: BARNSTEAD

WATERBODY: NA

Related Parties

AGENT

Name: FRAGGLE ROCK ENVIRONMENTAL SERVICES
Address: 38 GARLAND RD
Phone: 6039695574
Fax/Email: FREnvironmental@gmail.com

OWNER

Name: BETHEL BUILDERS LLC
Address: 184 VARNEY RD
Phone: 6377666141
Fax/Email: BETHALBUILDERS@YAHOO.COM

Requested Action:

Dredge and fill 275 square feet (SF) of palustrine forested wetland in order to install a 16-inch diameter by 20-foot-long culvert and construct a 15-foot-wide driveway with associated side slopes to provide access to a proposed single family residence.

NA

APPROVE PERMIT

Dredge and fill 275 square feet (SF) of palustrine forested wetland in order to install a 16-inch diameter by 20-foot-long culvert and construct a 15-foot-wide driveway with associated side slopes to provide access to a proposed single family residence.

With Conditions:

1. In accordance with Env-Wt 307.16 and Env-Wt 524.05(b), all work shall be done in accordance with the approved plans dated August 04, 2020 by Fraggie Rock Environmental, as received by the NH Department of Environmental Services (NHDES) on August 12, 2020 and the approved construction sequence as received electronically by NHDES on September 11, 2020.
2. In accordance with Env-Wt 310.03(a), no other work shall be done on the subject property pursuant to another expedited permit (EXP) or a statutory permit-by-notification (SPN) for a period of 12 months from the date the EXP was issued unless the property owner submits information, including a plan, to demonstrate that the proposed work is wholly unrelated to and separate from the work already done under the EXP or SPN; and the proposed work and the work already done under the EXP or SPN do not, when combined, constitute a project for which a standard permit is required.
3. In accordance with Env-Wt 524.05(a), residential, commercial, or industrial development projects in non-tidal wetlands shall submit a construction notice with the department at least 48 hours prior to

commencing work.

4. In accordance with Env-Wt 310.03(b), the work shall comply with all applicable conditions specified in Env-Wt 307.

5. In accordance with Env-Wt 307.10(b), work shall be done during low flow or in the dry unless a dredge dewatering, diversion, or cofferdam plan has been approved as part of the project.

6. In accordance with Env-Wt 307.11(d), no fill shall be allowed to achieve setbacks to septic systems specified in Env-Wq 1000.

7. In accordance with Env-Wt 307.11(b), limits of fill shall be clearly identified prior to commencement of work and controlled in accordance with Env-Wt 307.03 to ensure that fill does not spill over or erode into any area where filling is not authorized.

8. In accordance with Env-Wt 307.03(a), no activity shall be conducted in such a way as to cause or contribute to any violation of surface water quality standards specified in RSA 485-A:8 or Env-Wq 1700; ambient groundwater quality standards established under RSA 485-C; limitations on activities in a sanitary protective area established under Env-Dw 302.10 or Env-Dw 305.10; or any provision of RSA 485-A, Env-Wq 1000, RSA 483-B, or Env-Wq 1400 that protects water quality.

9. In accordance with Env-Wt 307.03(b), all work, including management of soil stockpiles, shall be conducted so as to minimize erosion, minimize sediment transfer to surface waters or wetlands, and minimize turbidity in surface waters and wetlands using the techniques described in Env-Wq 1505.02, Env-Wq 1505.04, Env-Wq 1506, and Env-Wq 1508; the applicable BMP manual; or a combination thereof, if the BMP manual provides less protection to jurisdictional areas than the provisions of Env-Wq 1500.

10. In accordance with Env-Wt 307.03(c)(1), water quality control measures shall be selected and implemented based on the size and nature of the project and the physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to jurisdictional areas.

11. In accordance with Env-Wt 307.03(c)(3), water quality control measures shall be installed prior to start of work and in accordance with the manufacturer's recommended specifications or, if none, the applicable requirements of Env-Wq 1506 or Env-Wq 1508.

12. In accordance with Env-Wt 307.03(c)(4), water quality control measures shall be capable of minimizing erosion; collecting sediment and suspended and floating materials; and filtering fine sediment.

13. In accordance with Env-Wt 307.03(c)(5), water quality control measures shall be maintained so as to ensure continued effectiveness in minimizing erosion and retaining sediment on-site during and after construction.

14. In accordance with Env-Wt 307.03(d), any sediment collected by water quality control measures shall be removed with sufficient frequency to prevent the discharge of sediment; and placed in an upland location in a manner that prevents its erosion into a surface water or wetland.

15. In accordance with Env-Wt 307.03(c)(6), water quality control measures shall remain in place until all disturbed surfaces are stabilized to a condition in which soils on the site will not experience accelerated or unnatural erosion by achieving and maintaining a minimum of 85% vegetative cover using an erosion control seed mix, whether applied in a blanket or otherwise, that is certified by its manufacturer as not containing any invasive species; or placing and maintaining a minimum of 3 inches of non-erosive material such as stone.

16. In accordance with Env-Wt 307.03(c)(7), temporary water quality control methods shall be removed upon completion of work when compliance with Env-Wt 307.03(c)(6) is achieved.

17. In accordance with Env-Wt 307.15(a), heavy equipment shall not be operated in any jurisdictional area unless specifically authorized by this permit.

18. In accordance with Env-Wt 307.11(a), fill shall be clean sand, gravel, rock, or other material that meets the project's specifications for its use; and does not contain any material that could contaminate surface

or groundwater or otherwise adversely affect the ecosystem in which it is used.

19. In accordance with Env-Wt 307.11(e), fill shall be not placed so as to direct flows onto adjacent or down-current property.

20. In accordance with Env-Wt 307.05(e), to prevent the use of soil or seed stock containing nuisance or invasive species, the contractor responsible for work shall follow Best Management Practices for the Control of Invasive and Noxious Plant Species (Invasive Plant BMPs).

21. In accordance with Env-Wt 307.12(a), within 3 days of final grading or temporary suspension of work in an area that is in or adjacent to surface waters, all exposed soil areas shall be stabilized by seeding and mulching, if during the growing season; or mulching with tackifiers on slopes less than 3:1 or netting and pinning on slopes steeper than 3:1 if not within the growing season.

With Findings:

1. This is classified as a minimum impact project per Rule Env-Wt 524.06(a), as the project meets all of the criteria for a residential development and per Rule Env-Wt 407.03(a), as impacts to jurisdictional areas other than a watercourse are less than 3,000 square feet (SF), and the project is not subject to an adjustment under Env-Wt 407.02; does not qualify for a project-type exception (PTE) under Env-Wt 407.04; and does not qualify for project-specific size criteria as identified in Env-Wt 407.04, Table 407-2.

2. Per Rule Env-Wt 306.05, the applicant has addressed all of the required planning items that are used to determine the appropriate impact classification of a project and the type of approval required.

3. Per Rule Env-Wt 310.01(d)(4), the applicant provided a signed statement certifying that the proposal is the alternative with the least adverse impact to jurisdictional areas, as required by Env-Wt 313.03.

4. Per Rule Env-Wt 310.01(h), the application for this expedited permit (EXP) included a signed statement from the municipal conservation commission certifying that the conservation commission waives its right to intervene on the project.

5. The residential development project meets the all of the approval criteria established in Env-Wt 524.02.

6. Per Rule Env-Wt 202.01(b) and as required by RSA 482-A:8, NHDES finds that the requirements for a public hearing do not apply as the project will not have a significant environmental impact, as defined in Env-Wt 104.19, on the resources protected by RSA 482-A, or, is not of substantial public interest, as defined in Env-Wt 104.32.

7. Per Rule Env-Wt 202.01(a), the department finds the project is clearly defined, therefore no hearing is required, as contemplated by RSA 482-A:3, XIV(a)(3)(C) or RSA 482-A:3, XIV(a)(4)(C).

8. Per Rule with Env-Wt 406.03(b), a delineation of wetlands, including vernal pools, was not required outside the limits of wetland impact for this project.

PERMIT TYPE: WETLAND PBN

PERMIT CATEGORY: WETLAND PBN

2020-02035

OWNER: COUNTRY ROAD REVOC TRUST

TOWN: NEWBURY

WATERBODY: SUNAPEE LAKE

Related Parties

OWNER

Name: COUNTRY ROAD REVOC TRUST
Address: 21 KENILWORTH RD
Phone:
Fax/Email:

Requested Action:

Temporarily impact 226 square feet along 20 linear feet of bank in order to repair and existing retaining wall along 1,723 feet of frontage on Lake Sunapee in Newbury.

NA

PBN IS COMPLETE

Temporarily impact 226 square feet along 20 linear feet of bank in order to repair and existing retaining wall along 1,723 feet of frontage on Lake Sunapee in Newbury.

With Conditions:

1. All work shall be in accordance with plans by Watermark Marine Construction dated June 23, 2020 and revised through September 2, 2020, as received by the NH Department of Environmental Services (NHDES) on September 4, 2020 as required pursuant to Env-Wt 307.16.
2. Repair of the existing retaining wall shall be conducted in the dry and shall result in no change in height, length, location, or configuration in accordance with 514.07(a).
3. Pursuant to RSA 483-B:9,V, (a)(2)(d)(v), this permit does not authorize the removal of trees or saplings within the waterfront buffer that would result in a tree and sapling point score below the minimum required per RSA 483-B:9, V, (a)(2)(D)(iv).
4. All development activities associated with any project shall be conducted in compliance with applicable requirements of RSA 483-B and Env-Wq 1400 during and after construction as required pursuant to RSA 483-B:3.
5. Work shall be carried out in a time and manner such that there are no discharges in or to fish or shellfish spawning or nursery areas during spawning seasons as required pursuant to Env-Wt 307.04. Impacts to such areas shall be avoided or minimized to the maximum extent practicable during all other times of the year.
6. Work shall be carried out in a time and manner to avoid disturbances to migratory waterfowl breeding and nesting areas as required pursuant to Env-Wt 307.04. Impacts to such areas shall be avoided or minimized to the maximum extent practicable during all other times of the year.
7. Water quality control measures capable of minimizing erosion; collecting sediment and suspended and floating materials; and filtering fine sediment shall be selected and implemented as appropriate based on the size and nature of the project and the physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to jurisdictional areas as required pursuant to Env-Wt 307.03(c).
8. Water quality control measures shall be installed prior to start of work and in accordance with the

manufacturer's recommended specifications or, if none, the applicable requirements of Env-Wq 1506 or Env-Wq 1508, shall be maintained so as to ensure continued effectiveness in minimizing erosion and retaining sediment on-site during and after construction, and removed upon completion of work and the effective stabilization of disturbed surfaces as required pursuant to Env-Wt 307.03(c).

9. All dredged and excavated material and construction-related debris shall be placed outside of those areas subject to RSA 482-A or RSA-483-B unless a permit for the deposition of materials within those areas has been obtained as required per RSA 482-A:3 or RSA 483-B:5-b respectively.

10. No activity shall be conducted in such a way as to cause or contribute to any violation of surface water quality standards specified in RSA 485-A:8 or Env-Wq 1700; ambient groundwater quality standards established under RSA 485-C; limitations on activities in a sanitary protective area established under Env-Dw 302.10 or Env-Dw 305.10; or any provision of RSA 485-A, Env-Wq 1000, RSA 483-B, or Env-Wq 1400 that protects water quality as required pursuant to Env-Wt 307.03(a).

11. Pursuant to RSA 482-A:14, RSA 482-A:14-b, and RSA 482-A:14-c, NHDES is authorized to take appropriate compliance actions should it be determined that, based upon additional information which becomes available, any of the structures depicted as "existing" on the plans submitted by or on behalf of the permittee were not previously permitted or grandfathered.

With Findings:

The project is classified as a minimum impact per Administrative Rule Env-Wt 514.07(a)(3), repair of the existing retaining wall conducted in the dry and results in no change in height, length, location, or configuration.

PERMIT TYPE: WETLAND PBN

PERMIT CATEGORY: WETLAND PBN

2020-02171

OWNER: MICHAEL/PATRICIA GARRETT

TOWN: NEWBURY

WATERBODY: SUNAPEE LAKE

Related Parties

OWNER

Name: MICHAEL/PATRICIA GARRETT
Address: 21 MARY CATHERINE LN
Phone: 9784308554
Fax/Email:

Requested Action:

Repair an existing 10 foot, 6 inch x 25 foot dock supported by a 9 foot x 10 foot, 6 inch crib attached to the northern side of an existing boathouse along 115 feet of frontage on Lake Sunapee in Newbury.

NA

PBN IS COMPLETE

Repair an existing 10 foot, 6 inch x 25 foot dock supported by a 9 foot x 10 foot, 6 inch crib attached to the northern side of an existing boathouse along 115 feet of frontage on Lake Sunapee in Newbury.

With Conditions:

1. All work shall be done in accordance with plans by Dick Butterfield, dated August 15, 2020 as received by the NH Department of Environmental Services (NHDES) on August 31, 2020 as required pursuant to Env-Wt 307.16.
2. This permit shall not be effective until it has been recorded in the Merrimack County Registry of Deeds and a copy of the recorded permit has been provided to the department as required pursuant to RSA 482-A:3, and Env-Wt 314.02.
3. Only those structures shown on the approved plans shall be installed or constructed along this frontage as required per Env-Wt 513.22, (a).
4. Any subdivision of the property frontage will require removal of a sufficient portion of the docking structures to comply with the dock size and density requirements in effect at the time of the subdivision as required pursuant to Env-Wt 314.02.
5. Work authorized shall be carried out in accordance with Env-Wt 307 such that appropriate turbidity controls are in place to protect water quality, that no turbidity escapes the immediate dredge area, and that appropriate turbidity controls shall remain until suspended particles have settled and water at the work site has returned to normal clarity.
6. Water quality control measures capable of minimizing erosion; collecting sediment and suspended and floating materials; and filtering fine sediment shall be selected and implemented as appropriate based on the size and nature of the project and the physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to jurisdictional areas as required pursuant to Env-Wt 307.03(c).
7. Water quality control measures shall be installed prior to start of work and in accordance with the manufacturer's recommended specifications or, if none, the applicable requirements of Env-Wq 1506 or Env-Wq 1508, shall be maintained so as to ensure continued effectiveness in minimizing erosion and retaining sediment on-site during and after construction, and removed upon completion of work and the effective stabilization of disturbed surfaces as required pursuant to Env-Wt 307.03(c).
8. No activity shall be conducted in such a way as to cause or contribute to any violation of surface water quality standards specified in RSA 485-A:8 or Env-Wq 1700; ambient groundwater quality standards established under RSA 485-C; limitations on activities in a sanitary protective area established under Env-Dw 302.10 or Env-Dw 305.10; or any provision of RSA 485-A, Env-Wq 1000, RSA 483-B, or Env-Wq 1400 that protects water quality as required pursuant to Env-Wt 307.03(a).
9. Work shall be carried out in a time and manner such that there are no discharges in or to fish or shellfish spawning or nursery areas during spawning seasons as required pursuant to Env-Wt 307.04. Impacts to such areas shall be avoided or minimized to the maximum extent practicable during all other times of the year.
10. Work shall be carried out in a time and manner to avoid disturbances to migratory waterfowl breeding and nesting areas as required pursuant to Env-Wt 307.04. Impacts to such areas shall be avoided or

minimized to the maximum extent practicable during all other times of the year.

11. All development activities associated with any project shall be conducted in compliance with applicable requirements of RSA 483-B and Env-Wq 1400 during and after construction as required pursuant to RSA 483-B:3.

12. No construction, modification, or maintenance activity that is contrary to RSA 482-A:26 shall be conducted.

13. Owners of permanent docking structures which are not maintained so as to be structurally sound and usable for their intended purpose shall remove those docking structures in accordance with Env-Wt 513.22(c), to prevent hazards to public safety, navigation, and recreation.

14. Pursuant to RSA 482-A:14, RSA 482-A:14-b, and RSA 482-A:14-c, NHDES is authorized to take appropriate compliance actions should it be determined that, based upon additional information which becomes available, any of the structures depicted as "existing" on the plans submitted by or on behalf of the permittee were not previously permitted or grandfathered.

With Findings:

This is a minimum impact project per Administrative Rule Env-Wt 513.24(a)(2), for the repair or replacement of an existing legal docking structure.

PERMIT TYPE: WETLAND PBN

PERMIT CATEGORY: WETLAND PBN

2020-02200

OWNER: JAMES R IRWIN & SONS INC

TOWN: LACONIA

WATERBODY: LAKE WINNIPESAUKEE

Related Parties

OWNER

Name: JAMES R IRWIN & SONS INC

Address: PO BOX 6145

Phone: 6035246661

Fax/Email:

Requested Action:

Repair pilings and piers associated with a 579 linear foot commercial boathouse facility and adjacent 3 foot, 6 inch x 108 foot piling supported dock on 527 feet of frontage on Lake Winnepesaukee in Laconia in accordance with plans by Watermark Marine Construction dated August 20, 2020 as received by the NH Department of Environmental Services (NHDES) on September 1, 2020.

NA

PBN IS COMPLETE

Repair pilings and piers associated with a 579 linear foot commercial boathouse facility and adjacent 3 foot, 6 inch x 108 foot piling supported dock on 527 feet of frontage on Lake Winnepesaukee in Laconia in accordance with plans by Watermark Marine Construction dated August 20, 2020 as received by the NH Department of Environmental Services (NHDES) on September 1, 2020.

With Conditions:

1. All work shall be done in accordance with plans by Watermark Marine Construction dated August 20, 2020, as received by the NH Department of Environmental Services (NHDES) on September 1, 2020 as required pursuant to Env-Wt 307.16.
2. This permit shall not be effective until it has been recorded in the Belknap County Registry of Deeds and a copy of the recorded permit has been provided to the department as required pursuant to RSA 482-A:3, and Env-Wt 314.02.
3. Any subdivision of the property frontage will require removal of a sufficient portion of the docking structures to comply with the dock size and density requirements in effect at the time of the subdivision as required to maintain compliance with Env-Wt 314.02 and Env-Wt 513.12.
4. Work authorized shall be carried out in accordance with Env-Wt 307 such that appropriate turbidity controls are in place to protect water quality, that no turbidity escapes the immediate dredge area, and that appropriate turbidity controls shall remain until suspended particles have settled and water at the work site has returned to normal clarity.
5. Water quality control measures capable of minimizing erosion; collecting sediment and suspended and floating materials; and filtering fine sediment shall be selected and implemented as appropriate based on the size and nature of the project and the physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to jurisdictional areas as required pursuant to Env-Wt 307.03(c).
6. Water quality control measures shall be installed prior to start of work and in accordance with the manufacturer's recommended specifications or, if none, the applicable requirements of Env-Wq 1506 or Env-Wq 1508, shall be maintained so as to ensure continued effectiveness in minimizing erosion and retaining sediment on-site during and after construction, and removed upon completion of work and the effective stabilization of disturbed surfaces as required pursuant to Env-Wt 307.03(c).
7. No activity shall be conducted in such a way as to cause or contribute to any violation of surface water quality standards specified in RSA 485-A:8 or Env-Wq 1700; ambient groundwater quality standards established under RSA 485-C; limitations on activities in a sanitary protective area established under Env-Dw 302.10 or Env-Dw 305.10; or any provision of RSA 485-A, Env-Wq 1000, RSA 483-B, or Env-Wq 1400 that protects water quality as required pursuant to Env-Wt 307.03(a).
8. Work shall be carried out in a time and manner such that there are no discharges in or to fish or shellfish spawning or nursery areas during spawning seasons as required pursuant to Env-Wt 307.04. Impacts to such areas shall be avoided or minimized to the maximum extent practicable during all other times of the year.
9. Work shall be carried out in a time and manner to avoid disturbances to migratory waterfowl breeding and nesting areas as required pursuant to Env-Wt 307.04. Impacts to such areas shall be avoided or minimized to the maximum extent practicable during all other times of the year.
10. All development activities associated with any project shall be conducted in compliance with

applicable requirements of RSA 483-B and Env-Wq 1400 during and after construction as required pursuant to RSA 483-B:3.

11. Owners of permanent docking structures which are not maintained so as to be structurally sound and usable for their intended purpose shall remove those docking structures in accordance with Env-Wt 513.22(c), to prevent hazards to public safety, navigation, and recreation.

12. Pursuant to RSA 482-A:14, RSA 482-A:14-b, and RSA 482-A:14-c, NHDES is authorized to take appropriate compliance actions should it be determined that, based upon additional information which becomes available, any of the structures depicted as "existing" on the plans submitted by or on behalf of the permittee were not previously permitted or grandfathered.

With Findings:

The project is classified as a minimum impact per Administrative Rule Env-Wt 515.07(a), for the maintenance and repair of any boathouse.

PERMIT TYPE: SHORELAND STANDARD

PERMIT CATEGORY: SHORELAND STANDARD

2020-00389

OWNER: KAREN M/ROBERT P BEAUDET

TOWN: BELMONT

WATERBODY: SARGENT LAKE

Related Parties

AGENT

Name: BRYAN L BAILEY ASSOCIATES INC
Address: 217 COTTON HILL RD
Phone: 6035283734
Fax/Email:

OWNER

Name: KAREN M/ROBERT P BEAUDET
Address: 15 RIDGEVIEW DR
Phone: 6034931457
Fax/Email: RBEAUDET@MANCHESTER.GOV

PREVOWNER

Name: JANINE/ROBERT NORKIEWICZ
Address: 59 SARGENT LAKE RD
Phone: 9788153070
Fax/Email: B52NORK@METROCAST.NET

Requested Action:

Request name change to Karen M./Robert P. Beaudet to impact 7,330 square feet of protected shoreland in order to construct a 2 bedroom structure with an on-site septic system, driveway, and a 6 foot path toward the water.

Waiver Granted: The requirement to reduce the Woodland Buffer per RSA 483-B:9, V, (b), (2), (A) where construction of a septic system will result in less than 25% of woodland buffer to be maintained between 50 feet and 150 feet of the referenced line is waived.

NA

APPROVE NAME CHANGE

Change name and address to Karen M./Robert P. Beaudet 15 Ridgeview Drive Hooksett NH 03106 to impact 7,330 square feet of protected shoreland in order to construct a 2 bedroom structure with an on-site septic system, driveway, and a 6 foot path toward the water.

Waiver Granted: The requirement to reduce the Woodland Buffer per RSA 483-B:9, V, (b), (2), (A) where construction of a septic system will result in less than 25% of woodland buffer to be maintained between 50 feet and 150 feet of the referenced line is waived.

With Conditions:

All work shall be in accordance with plans by Bryan L. Bailey Associates, Inc. dated February 21, 2020 and received by the NH Department of Environmental Services (NHDES) on March 3, 2020.

Neither the new primary structure nor the proposed septic system may be constructed until the system is

approved by the NHDES Subsurface Systems Bureau.

Orange construction fencing shall be installed at the limits of the temporary impact area as shown on the approved plans prior to the start of work and shall be maintained throughout the project in order to prevent accidental encroachment into areas in which impacts have not been approved.

No more than 18.5% of the area of the lot within the protected shoreland shall be covered by impervious surfaces unless additional approval is obtained from NHDES.

Native vegetation within an area of at least 976 square feet within the Natural Woodland Buffer located between 50 and 150 feet landward of the reference line shall be retained in an unaltered state in order to comply with RSA 483-B:9, V, (b), (2).

This permit does not authorize the removal of trees or saplings within the waterfront buffer that would result in a tree and sapling point score below the minimum required per RSA 483-B:9, V, (a), (2), (D), (iv).

Erosion and siltation control measures shall be installed prior to the start of work, be maintained throughout the project, and remain in place until all disturbed surfaces are stabilized.

Erosion and siltation controls shall be appropriate to the size and nature of the project and to the physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to wetlands or surface waters.

No person undertaking any activity in the protected shoreland shall cause or contribute to, or allow the activity to cause or contribute to, any violations of the surface water quality standards established in Env-Wq 1700.

Any fill used shall be clean sand, gravel, rock, or other suitable material.

Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.

This permit shall not preclude NHDES from taking any enforcement or revocation action if NHDES later determines that any of the structures depicted as "existing" on the plans submitted by the applicant were not previously permitted or grandfathered.

PERMIT TYPE: SHORELAND STANDARD

PERMIT CATEGORY: SHORELAND STANDARD

2020-01291

OWNER: ALAN WYSOCKI

TOWN: NEW DURHAM

WATERBODY: MERRYMEETING LAKE

Related Parties

AGENT

Name: VARNEY ENGINEERING LLC
Address: 93 POWDER MILL RD
Phone: 6038757110
Fax/Email:

OWNER

Name: ALAN WYSOCKI
Address: PO BOX 151
Phone: 6035452078
Fax/Email: ALANHENRYW@GMAIL.COM

Requested Action:

Impact 5,958 square feet of protected shoreland to construct a single family primary structure with attached deck, driveway and septic system; plus a walkway and pervious patio.

NA

APPROVE PERMIT

Impact 5,958 square feet of protected shoreland to construct a single family primary structure with attached deck, driveway and septic system; plus a walkway and pervious patio.

With Conditions:

1. All work shall be in accordance with plans by Varney Engineering, LLC dated March 16, 2020 and revised through July 14, 2020, as received by the NH Department of Environmental Services (NHDES) on August 14, 2020.
2. The proposed foundation shall not be constructed until any approval as may be required under RSA 485-A and Rules Env-Wq 1000 is obtained from NHDES Subsurface Systems Bureau.
3. Orange construction fencing shall be installed at the limits of the temporary impact area as shown on the approved plans prior to the start of work and shall be maintained throughout the project in order to prevent accidental encroachment into areas in which impacts have not been approved as required per Rule Env-Wq 1406.20, (e).
4. No more than 12.5% of the area of the lot within the protected shoreland shall be covered by impervious surfaces unless additional approval is obtained from NHDES in order to ensure compliance with RSA 483-B:9, V, (g).
5. Native vegetation within an area of at least 1,880 square feet within the Woodland Buffer located between 50 and 150 feet landward of the reference line shall be retained as natural woodlands in an unaltered state in order to comply with RSA 483-B:9, V, (b), (2).
6. The proposed stormwater management structures shall be installed and maintained to effectively absorb and infiltrate stormwater in order to ensure compliance with RSA 483-B:9, V, (g).

7. All pervious technologies used shall be installed and maintained to effectively absorb and infiltrate stormwater as required per RSA 483-B:6, II and Rule Env-Wq 1406.15, (c) in order to ensure compliance with RSA 483-B:9, V, (g).
8. No person undertaking any activity in the protected shoreland shall cause or contribute to, or allow the activity to cause or contribute to, any violations of the surface water quality standards established in Env-Wq 1700 as required per Rule Env-Wq 1406.20, (c).
9. Erosion and siltation control measures shall be installed prior to the start of work, be maintained throughout the project, and remain in place until all disturbed surfaces are stabilized as required per Rule Env-Wq 1406.20, (a).
10. Erosion and siltation controls shall be appropriate to the size and nature of the project and to the physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to wetlands or surface waters as required per Rule Env-Wq 1406.20, (b).
11. The individual responsible for completion of the work shall utilize techniques described in the New Hampshire Stormwater Manual, Volume 3, Erosion and Sediment Controls During Construction (December 2008) as required pursuant to RSA 483-B:9, V, (d) Erosion and Siltation, (1).
12. This permit shall not be interpreted as acceptance or approval of any impact that will occur within wetlands jurisdiction regulated under RSA 482-A including all wetlands, surface waters and their banks, the tidal-buffer zone, and sand dunes. The owner is responsible for maintaining compliance with RSA 482-A and Administrative Rules Env-Wt 100 - 900 and obtaining any Wetland Impact Permit that may be required prior to construction, excavation or fill that will occur within Wetlands jurisdiction.
13. This permit shall not preclude NHDES from taking any enforcement or revocation action as authorized pursuant to 483-B:5, I, if NHDES later determines that any of the structures depicted as "existing" on the plans submitted by the applicant were not previously permitted or grandfathered.

PERMIT TYPE: SHORELAND STANDARD

PERMIT CATEGORY: SHORELAND STANDARD

2020-01716

OWNER: STEPHEN/WENDY GILCHRIST

TOWN: BRIDGEWATER

WATERBODY: NEWFOUND LAKE

Related Parties

AGENT

Name: B A BARNARD ENT INC
Address: 34 PINE TOP LN
Phone: 6037442696
Fax/Email: babarnard@metrocast.net

OWNER

Name: STEPHEN/WENDY GILCHRIST
Address: 90 SHERBURNE AVE
Phone:
Fax/Email:

Requested Action:

Impact 10,193 square feet of protected shoreland in order remove primary structure and driveway to construct a primary structure with a porch, stairs with a retaining wall, an attached garage, and a reconfigured driveway with a retaining wall and stormwater management, landscaping, and install a septic system.

NA

APPROVE PERMIT

Impact 10,193 square feet of protected shoreland in order remove primary structure and driveway to construct a primary structure with a porch, stairs with a retaining wall, an attached garage, and a reconfigured driveway with a retaining wall and stormwater management, landscaping, and install a septic system.

With Conditions:

1. All work shall be in accordance with plans by B. A. Barnard Ent., Inc. dated August 2020 as revised and received by the NH Department of Environmental Services (NHDES) on August 26, 2020 pursuant to 483-B:5-b Permit Required; Exemption, I, (a).
2. Neither the new primary structure nor the proposed septic system may be constructed until the system is approved by the NHDES Subsurface Systems Bureau as required pursuant to RSA 483-B:6, I, (c).
3. Orange construction fencing shall be installed at the limits of the temporary impact area as shown on the approved plans prior to the start of work and shall be maintained throughout the project in order to prevent accidental encroachment into areas in which impacts have not been approved as required per Rule Env-Wq 1406.20, (e).
4. No more than 26.3% of the area of the lot within the protected shoreland shall be covered by impervious surfaces unless additional approval is obtained from NHDES in order to ensure compliance with RSA 483-B:9, V, (g).
5. Native vegetation within an area of at least 903 square feet within the Woodland Buffer located

between 50 and 150 feet landward of the reference line shall be retained as natural woodlands in an unaltered state in order to comply with RSA 483-B:9, V, (b), (2).

6. Erosion and siltation control measures shall be installed prior to the start of work, be maintained throughout the project, and remain in place until all disturbed surfaces are stabilized as required per Rule Env-Wq 1406.20, (a).

7. Erosion and siltation controls shall be appropriate to the size and nature of the project and to the physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to wetlands or surface waters as required per Rule Env-Wq 1406.20, (b).

8. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1 as required pursuant to RSA 483-B:9, V, (d) Erosion and Siltation, (1).

9. Any fill used shall be clean sand, gravel, rock, or other suitable material as required per Rule Env-Wq 1406.20, (d).

10. No person undertaking any activity in the protected shoreland shall cause or contribute to, or allow the activity to cause or contribute to, any violations of the surface water quality standards established in Env-Wq 1700 as required per Rule Env-Wq 1406.20, (c).

11. All pervious technologies used shall be installed and maintained to effectively absorb and infiltrate stormwater as required per RSA 483-B:6, II and Rule Env-Wq 1406.15, (c) in order to ensure compliance with RSA 483-B:9, V, (g).

12. The proposed infiltration trench adjacent to the driveway shall be installed and maintained to effectively absorb and infiltrate stormwater in order to ensure compliance with RSA 483-B:9, V, (g).

13. Photographs documenting the construction of the proposed infiltration trench shall be submitted to the Department prior to any party taking up occupancy of the new residential primary structure as required per RSA 483-B:6, II and Rule Env-Wq 1406.15, (c) in order to ensure compliance with RSA 483-B:9, V, (g).

14. This permit shall not be interpreted as acceptance or approval of any impact that will occur within wetlands jurisdiction regulated under RSA 482-A including all wetlands, surface waters and their banks, the tidal-buffer zone, and sand dunes. The owner is responsible for maintaining compliance with RSA 482-A and Administrative Rules Env-Wt 100 - 900 and obtaining any Wetland Impact Permit that may be required prior to construction, excavation or fill that will occur within Wetlands jurisdiction as required pursuant to RSA 483-B:6, I, (c).

15. This permit shall not preclude NHDES from taking any enforcement or revocation action as authorized pursuant to 483-B:5, I, if NHDES later determines that any of the structures depicted as "existing" on the plans submitted by the applicant were not previously permitted or grandfathered.

PERMIT TYPE: SHORELAND STANDARD

PERMIT CATEGORY: SHORELAND STANDARD

2020-01954

OWNER: THE HORNE FAMILY TRUST

TOWN: NORTHWOOD

WATERBODY: NORTHWOOD LAKE

Related Parties

OWNER

Name: THE HORNE FAMILY TRUST
Address: 1 MONROE DR
Phone: 6035409608
Fax/Email: HORNEMW@GMAIL.COM

Requested Action:

Move a 24 foot x 28 foot seasonal camp away from the lake, raise the structure 4 feet, construct a concrete foundation under it while adding a 12 foot x 12 foot addition and construct a replacement septic system with pump up to leachfield.

NA

APPROVE PERMIT

Move a 24 foot x 28 foot seasonal camp away from the lake, raise the structure 4 feet, construct a concrete foundation under it while adding a 12 foot x 12 foot addition and construct a replacement septic system with pump up to leachfield.

With Conditions:

1. All work shall be in accordance with plans by Keyland Enterprises, LLC dated August 3, 2020 and received by the NH Department of Environmental Services (NHDES) on August 10, 2020 pursuant to 483-B:5-b Permit Required; Exemption, I, (a).
2. The proposed septic system shall not be constructed until the system is approved by the NHDES Subsurface Systems Bureau as required pursuant to RSA 483-B:6, I, (c).
3. Orange construction fencing shall be installed at the limits of the temporary impact area as shown on the approved plans prior to the start of work and shall be maintained throughout the project in order to prevent accidental encroachment into areas in which impacts have not been approved as required per Rule Env-Wq 1406.20, (e).
4. No more than 19.3% of the area of the lot within the protected shoreland shall be covered by impervious surfaces unless additional approval is obtained from NHDES in order to ensure compliance with RSA 483-B:9, V, (g).
5. Native vegetation within an area of at least 1,065 square feet within the Woodland Buffer located between 50 and 150 feet landward of the reference line shall be retained as natural woodlands in an unaltered state in order to comply with RSA 483-B:9, V, (b), (2).
6. Erosion and siltation control measures shall be installed prior to the start of work, be maintained throughout the project, and remain in place until all disturbed surfaces are stabilized as required per Rule Env-Wq 1406.20, (a).
7. Erosion and siltation controls shall be appropriate to the size and nature of the project and to the

physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to wetlands or surface waters as required per Rule Env-Wq 1406.20, (b).

8. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1 as required pursuant to RSA 483-B:9, V, (d) Erosion and Siltation, (1).

9. Any fill used shall be clean sand, gravel, rock, or other suitable material as required per Rule Env-Wq 1406.20, (d).

10. No person undertaking any activity in the protected shoreland shall cause or contribute to, or allow the activity to cause or contribute to, any violations of the surface water quality standards established in Env-Wq 1700 as required per Rule Env-Wq 1406.20, (c).

11. This permit shall not preclude NHDES from taking any enforcement or revocation action as authorized pursuant to 483-B:5, I, if NHDES later determines that any of the structures depicted as "existing" on the plans submitted by the applicant were not previously permitted or grandfathered.

PERMIT TYPE: SHORELAND STANDARD

PERMIT CATEGORY: SHORELAND STANDARD

2020-01975

OWNER: WILLIAM KICZUK

TOWN: ALTON

WATERBODY: LAKE WINNIPESAUKEE

Related Parties

AGENT

Name: BELKNAP LANDSCAPE COMPANY INC
Address: 25 COUNTRY CLUB RD UNIT 101
Phone: 6034555907
Fax/Email: steph@belknaplandscape.com

OWNER

Name: WILLIAM KICZUK
Address: 64 PIPERS PT LN
Phone: 6032133771
Fax/Email: BKICZUK@GMAIL.COM

Requested Action:

Impact 9,196 square feet of protected shoreland in order to construct a fire pit with seating area, replace existing pervious patio with a new pervious surface material, rebuild existing retaining walls and walkway steps, install permeable patios under two existing decks and crushed stone under a third deck, vegetate areas with lawn and native plantings, and install a 50 square foot stormwater retention basin.

NA

Impact 9,196 square feet of protected shoreland in order to construct a fire pit with seating area, replace existing pervious patio with a new pervious surface material, rebuild existing retaining walls and walkway steps, install permeable patios under two existing decks and crushed stone under a third deck, vegetate areas with lawn and native plantings, and install a 50 square foot stormwater retention basin.

With Conditions:

1. All work shall be in accordance with plans by Belknap Landscape Co. Inc. dated August 4, 2020 and received by the NH Department of Environmental Services (NHDES) on August 11, 2020 pursuant to 483-B:5-b Permit Required; Exemption, I, (a).
2. Orange construction fencing shall be installed at the limits of the temporary impact area as shown on the approved plans prior to the start of work and shall be maintained throughout the project in order to prevent accidental encroachment into areas in which impacts have not been approved as required per Rule Env-Wq 1406.20, (e).
3. No more than 21.6% of the area of the lot within the protected shoreland shall be covered by impervious surfaces unless additional approval is obtained from NHDES in order to ensure compliance with RSA 483-B:9, V, (g).
4. Native vegetation within an area of at least 3,060 square feet within the Woodland Buffer located between 50 and 150 feet landward of the reference line shall be retained as natural woodlands in an unaltered state in order to comply with RSA 483-B:9, V, (b), (2).
5. Erosion and siltation control measures shall be installed prior to the start of work, be maintained throughout the project, and remain in place until all disturbed surfaces are stabilized as required per Rule Env-Wq 1406.20, (a).
6. Erosion and siltation controls shall be appropriate to the size and nature of the project and to the physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to wetlands or surface waters as required per Rule Env-Wq 1406.20, (b).
7. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1 as required pursuant to RSA 483-B:9, V, (d) Erosion and Siltation, (1).
8. Any fill used shall be clean sand, gravel, rock, or other suitable material as required per Rule Env-Wq 1406.20, (d).
9. No person undertaking any activity in the protected shoreland shall cause or contribute to, or allow the activity to cause or contribute to, any violations of the surface water quality standards established in Env-

Wq 1700 as required per Rule Env-Wq 1406.20, (c).

10. All pervious technologies used shall be installed and maintained to effectively absorb and infiltrate stormwater as required per RSA 483-B:6, II and Rule Env-Wq 1406.15, (c) in order to ensure compliance with RSA 483-B:9, V, (g).

11. This permit shall not preclude NHDES from taking any enforcement or revocation action as authorized pursuant to 483-B:5, I, if NHDES later determines that any of the structures depicted as "existing" on the plans submitted by the applicant were not previously permitted or grandfathered.

PERMIT TYPE: SHORELAND STANDARD

PERMIT CATEGORY: SHORELAND STANDARD

2020-01980

OWNER: WHEELER/WILLITS REVOCABLE TRUST

TOWN: GREENFIELD

WATERBODY: SUNSET LAKE

Related Parties

AGENT

Name: BRIAN HALVONIK
Address: 280 NELSON RD
Phone: 6038273605
Fax/Email: BRIANHALVONIK63@GMAIL.COM

OWNER

Name: WHEELER/WILLITS REVOCABLE TRUST
Address: 39 MASSASOIT ST
Phone: 4135381744
Fax/Email: WILLITS1@COMCAST.NET

Requested Action:

Impact 256 square feet of protected shoreland in order to construct an addition onto the nonconforming primary structure.

NA

APPROVE PERMIT

Impact 256 square feet of protected shoreland in order to construct an addition onto the nonconforming primary structure.

With Conditions:

1. All work shall be in accordance with plans by Tom Willits dated August 5, 2020 and received by the NH Department of Environmental Services (NHDES) on August 11, 2020 pursuant to 483-B:5-b Permit Required; Exemption, I, (a).
2. Orange construction fencing shall be installed at the limits of the temporary impact area as shown on the approved plans prior to the start of work and shall be maintained throughout the project in order to prevent accidental encroachment into areas in which impacts have not been approved as required per Rule Env-Wq 1406.20, (e).
3. No more than 12.8 % of the area of the lot within the protected shoreland shall be covered by impervious surfaces unless additional approval is obtained from NHDES in order to ensure compliance with RSA 483-B:9, V, (g).
4. Native vegetation within an area of at least 1,500 square feet within the Woodland Buffer located between 50 and 150 feet landward of the reference line shall be retained as natural woodlands in an unaltered state in order to comply with RSA 483-B:9, V, (b), (2).
5. Erosion and siltation control measures shall be installed prior to the start of work, be maintained throughout the project, and remain in place until all disturbed surfaces are stabilized as required per Rule Env-Wq 1406.20, (a).
6. Erosion and siltation controls shall be appropriate to the size and nature of the project and to the physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to wetlands or surface waters as required per Rule Env-Wq 1406.20, (b).
7. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1 as required pursuant to RSA 483-B:9, V, (d) Erosion and Siltation, (1).
8. Any fill used shall be clean sand, gravel, rock, or other suitable material as required per Rule Env-Wq 1406.20, (d).
9. No person undertaking any activity in the protected shoreland shall cause or contribute to, or allow the activity to cause or contribute to, any violations of the surface water quality standards established in Env-Wq 1700 as required per Rule Env-Wq 1406.20, (c).
10. This permit shall not be interpreted as acceptance or approval of any impact that will occur within wetlands jurisdiction regulated under RSA 482-A including all wetlands, surface waters and their banks, the tidal-buffer zone, and sand dunes. The owner is responsible for maintaining compliance with RSA 482-A and Administrative Rules Env-Wt 100 - 900 and obtaining any Wetland Impact Permit that may be required prior to construction, excavation or fill that will occur within Wetlands jurisdiction as required pursuant to RSA 483-B:6, I, (c).
11. This permit shall not preclude NHDES from taking any enforcement or revocation action as authorized pursuant to 483-B:5, I, if NHDES later determines that any of the structures depicted as "existing" on the plans submitted by the applicant were not previously permitted or grandfathered.

2. Neither the new primary structure nor the proposed septic system may be constructed until the system is approved by the NHDES Subsurface Systems Bureau as required pursuant to RSA 483-B:6, I, (c).
3. Orange construction fencing shall be installed at the limits of the temporary impact area as shown on the approved plans prior to the start of work and shall be maintained throughout the project in order to prevent accidental encroachment into areas in which impacts have not been approved as required per Rule Env-Wq 1406.20, (e).
4. No more than 37.3% of the area of the lot within the protected shoreland shall be covered by impervious surfaces unless additional approval is obtained from NHDES in order to ensure compliance with RSA 483-B:9, V, (g).
5. Native vegetation within an area of at least 80 square feet within the Woodland Buffer located between 50 and 150 feet landward of the reference line shall be retained as natural woodlands in an unaltered state in order to comply with RSA 483-B:9, V, (b), (2).
6. Pursuant to RSA 483-B:9, V, (b), (2), no native vegetation shall be removed from within the Natural Woodland Buffer located between 50 and 150 feet landward of the reference line.
7. Erosion and siltation control measures shall be installed prior to the start of work, be maintained throughout the project, and remain in place until all disturbed surfaces are stabilized as required per Rule Env-Wq 1406.20, (a).
8. Erosion and siltation controls shall be appropriate to the size and nature of the project and to the physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to wetlands or surface waters as required per Rule Env-Wq 1406.20, (b).
9. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1 as required pursuant to RSA 483-B:9, V, (d) Erosion and Siltation, (1).
10. Any fill used shall be clean sand, gravel, rock, or other suitable material as required per Rule Env-Wq 1406.20, (d).
11. No person undertaking any activity in the protected shoreland shall cause or contribute to, or allow the activity to cause or contribute to, any violations of the surface water quality standards established in Env-Wq 1700 as required per Rule Env-Wq 1406.20, (c).
12. All pervious technologies used shall be installed and maintained to effectively absorb and infiltrate stormwater as required per RSA 483-B:6, II and Rule Env-Wq 1406.15, (c) in order to ensure compliance with RSA 483-B:9, V, (g).
13. This permit shall not be interpreted as acceptance or approval of any impact that will occur within wetlands jurisdiction regulated under RSA 482-A including all wetlands, surface waters and their banks, the tidal-buffer zone, and sand dunes. The owner is responsible for maintaining compliance with RSA 482-A and Administrative Rules Env-Wt 100 - 900 and obtaining any Wetland Impact Permit that may be required prior to construction, excavation or fill that will occur within Wetlands jurisdiction as required pursuant to RSA 483-B:6, I, (c).
14. This permit shall not preclude NHDES from taking any enforcement or revocation action as authorized pursuant to 483-B:5, I, if NHDES later determines that any of the structures depicted as "existing" on the plans submitted by the applicant were not previously permitted or grandfathered.

PERMIT TYPE: SHORELAND STANDARD
PERMIT CATEGORY: SHORELAND STANDARD

2020-02008 **OWNER: EDGEWATER HOLDINGS NH LLC**

TOWN: MOULTONBOROUGH **WATERBODY: LAKE WINNIPESAUKEE**

Related Parties

AGENT

Name: YERKES SURVEYING ASSOCIATES
Address: PO BOX 38
Phone: 6035245117
Fax/Email: FYERKES@YERKES-SURVEYING.COM

OWNER

Name: EDGEWATER HOLDINGS NH LLC
Address: 209 SCHUYLER RD
Phone:
Fax/Email:

Requested Action:

Impact 17,315 square feet of protected shoreland in order to construct a 4 bedroom primary structure with a deck, driveway, septic and well on a vacant lot.

NA

APPROVE PERMIT

Impact 17,315 square feet of protected shoreland in order to construct a 4 bedroom primary structure with a deck, driveway, septic and well on a vacant lot.

With Conditions:

1. All work shall be in accordance with plans by Yerkes Survey Associates, LLC dated July 27, 2020 and received by the NH Department of Environmental Services (NHDES) on August 17, 2020 pursuant to 483-B:5-b Permit Required; Exemption, I, (a).
2. Neither the new primary structure nor the proposed septic system may be constructed until the system is approved by the NHDES Subsurface Systems Bureau as required pursuant to RSA 483-B:6, I, (c).
3. Orange construction fencing shall be installed at the limits of the temporary impact area as shown on the approved plans prior to the start of work and shall be maintained throughout the project in order to

prevent accidental encroachment into areas in which impacts have not been approved as required per Rule Env-Wq 1406.20, (e).

4. No more than 16.4% of the area of the lot within the protected shoreland shall be covered by impervious surfaces unless additional approval is obtained from NHDES in order to ensure compliance with RSA 483-B:9, V, (g).

5. Native vegetation within an area of at least 4,414 square feet within the Woodland Buffer located between 50 and 150 feet landward of the reference line shall be retained as natural woodlands in an unaltered state in order to comply with RSA 483-B:9, V, (b), (2).

6. Erosion and siltation control measures shall be installed prior to the start of work, be maintained throughout the project, and remain in place until all disturbed surfaces are stabilized as required per Rule Env-Wq 1406.20, (a).

7. Erosion and siltation controls shall be appropriate to the size and nature of the project and to the physical characteristics of the site, including slope, soil type, vegetative cover, and proximity to wetlands or surface waters as required per Rule Env-Wq 1406.20, (b).

8. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1 as required pursuant to RSA 483-B:9, V, (d) Erosion and Siltation, (1).

9. Any fill used shall be clean sand, gravel, rock, or other suitable material as required per Rule Env-Wq 1406.20, (d).

10. No person undertaking any activity in the protected shoreland shall cause or contribute to, or allow the activity to cause or contribute to, any violations of the surface water quality standards established in Env-Wq 1700 as required per Rule Env-Wq 1406.20, (c).

11. This permit shall not be interpreted as acceptance or approval of any impact that will occur within wetlands jurisdiction regulated under RSA 482-A including all wetlands, surface waters and their banks. The owner is responsible for maintaining compliance with RSA 482-A and Administrative Rules Env-Wt 100 - 900 and obtaining any Wetland Impact Permit that may be required prior to construction, excavation or fill that will occur within Wetlands jurisdiction as required pursuant to RSA 483-B:6, I, (c).

12. This permit shall not preclude NHDES from taking any enforcement or revocation action as authorized pursuant to 483-B:5, I, if NHDES later determines that any of the structures depicted as "existing" on the plans submitted by the applicant were not previously permitted or grandfathered.

PERMIT TYPE: STATUTORY PERMIT BY NOTIFICATION

PERMIT CATEGORY: TRAILS SPN

2020-02069

OWNER: DWSX2 HOLDINGS LLC

TOWN: BARRINGTON

WATERBODY: NA

Related Parties

OWNER

Name: DWSX2 HOLDINGS LLC
Address: 270 BEAUTY HILL RD
Phone:
Fax/Email:

NA

COMPLETE NOTIFICATION
Construct two boardwalks.

PERMIT TYPE: STATUTORY PERMIT BY NOTIFICATION

PERMIT CATEGORY: FORESTRY SPN

2020-02137 OWNER: GRANITE FOREST TRUST

TOWN: ANDOVER

WATERBODY: NA

Related Parties

FORESTER

Name: RIVER EDGE FORESTRY
Address: PO BOX 1203
Phone: 6035269290
Fax/Email: JEEPS@TDS.NET

OWNER

Name: GRANITE FOREST TRUST
Address: 220 SAND HILL RD
Phone:
Fax/Email:

NA

COMPLETE NOTIFICATION

Andover Tax Map#23 Lot 611-532

PERMIT TYPE: STATUTORY PERMIT BY NOTIFICATION

PERMIT CATEGORY: FORESTRY SPN

2020-02287

OWNER: NEAL DELAGE

TOWN: CHICHESTER

WATERBODY: NA

Related Parties

FORESTER

Name: JEFFREY EAMES
Address: 168 GRANITE ST
Phone: 6034854459
Fax/Email: jeff@nhforestry.com

OWNER

Name: NEAL DELAGE
Address: 169 SUNCOOK VALLEY RD
Phone:
Fax/Email:

NA

COMPLETE NOTIFICATION

Chichester Tax Map #8, Lot #39

PERMIT TYPE: STATUTORY PERMIT BY NOTIFICATION

PERMIT CATEGORY: FORESTRY SPN

2020-02300

OWNER: CAROL S/CLYDE MARSH

TOWN: CROYDON

WATERBODY: NA

Related Parties

FORESTER

Name: RYAN GUMBART
Address: 1235 WEATHERSFIELD CENTER RD
Phone:
Fax/Email:

OWNER

Name: CAROL S/CLYDE MARSH
Address: PO BOX 253
Phone:
Fax/Email:

NA

COMPLETE NOTIFICATION

Croydon Tax Map #000011, Lot #000138-000000

PERMIT TYPE: STATUTORY PERMIT BY NOTIFICATION

PERMIT CATEGORY: CULVERT REPAIR AND REPLACEMENT SPN

2020-02290

OWNER: JOHN DOYLE

TOWN: NEW LONDON

WATERBODY: NA

Related Parties

AGENT

Name: GABE BOLIN
Address: 535 STONE CUTTERS WAY
Phone: 6038096101
Fax/Email: GBOLIN@STONE-ENV.COM

OWNER

Name: JOHN DOYLE
Address: 533 FOREST ACRES RD
Phone: 6035267850
Fax/Email:

NA

COMPLETE NOTIFICATION

Replace two 12 inch diameter culverts with a single 42 inch wide x 29 high elliptical culvert.

PERMIT TYPE: STATUTORY PERMIT BY NOTIFICATION

PERMIT CATEGORY: CULVERT REPAIR AND REPLACEMENT SPN

2020-02291

OWNER: JOHN DOYLE

TOWN: NEW LONDON

WATERBODY: NA

Related Parties

AGENT

Name: GABE BOLIN
Address: 535 STONE CUTTERS WAY
Phone: 6038096101
Fax/Email: GBOLIN@STONE-ENV.COM

OWNER

Name: JOHN DOYLE
Address: 533 FOREST ACRES RD
Phone: 6035267850
Fax/Email:

NA

COMPLETE NOTIFICATION

Replace two 15 inch diameter pipes with a single 57 inch wide x 38 inch high elliptical culvert.

PERMIT TYPE: STATUTORY PERMIT BY NOTIFICATION

PERMIT CATEGORY:

2020-01892

OWNER: JOHN H MORSE TRUST

TOWN: ORANGE

WATERBODY: NA

Related Parties

FORESTER

Name: JEFFREY SNITKIN
Address: 752 RT 103A
Phone: 8023100292
Fax/Email:

OWNER

Name: JOHN H MORSE TRUST
Address: 83 PATTERSON RD
Phone: 6035266386
Fax/Email:

NA

COMPLETE NOTIFICATION
Orange Tax Map #6, Lot #6