Appendix C. Deicing Application Rates and Documentation Form

Deicing Application Rate Guidelines

24' of pavement (typcial two-lane road)

These rates are not fixed values, but rather the middle of a range to be selected and adjusted by an agency according to its local conditions and experience.

			Pounds per two-lane mile					
Pavement Temp. (°F) and Trend (↑↓)	Weather Condition	Maintenance Actions	Salt Prewetted / Pretreated with Salt Brine	Salt Prewetted / Pretreated with Other Blends	Dry Salt*	Winter Sand (abrasives)		
>30° ↑	Snow	Plow, treat intersections only	80	70	100*	Not recommended		
	Freezing Rain	Apply Chemical	80 - 160	70 - 140	100 - 200*	Not recommended		
30° ↓	Snow	Plow and apply chemical	80 - 160	70 - 140	100 - 200*	Not recommended		
	Freezing Rain	Apply Chemical	150 - 200	130 - 180	180 - 240*	Not recommended		
25° - 30° 个	Snow	Plow and apply chemical	120 - 160	100 - 140	150 - 200*	Not recommended		
	Freezing Rain	Apply Chemical	150 - 200	130 - 180	180 - 240*	Not recommended		
25° - 30° ↓	Snow	Plow and apply chemical	120 - 160	100 - 140	150 - 200*	Not recommended		
	Freezing Rain	Apply Chemical	160 - 240	140 - 210	200 - 300*	400		
20° - 25° 个	Snow or Freezing Rain	Plow and apply chemical	160 - 240	140 - 210	200 - 300*	400		
20° - 25° ↓	Snow	Plow and apply chemical	200 - 280	175 - 250	250 - 350*	Not recommended		
	Freezing Rain	Apply Chemical	240 - 320	210 - 280	300 - 400*	400		
15° - 20° ↑	Snow	Plow and apply chemical	200 - 280	175 - 250	250 - 350*	Not recommended		
13 - 20	Freezing Rain	Apply Chemical	240 - 320	210 - 280	300 - 400*	400		
15° - 20° ↓	Snow or Freezing Rain	Plow and apply chemical	240 - 320	210 - 280	300 - 400*	500 for freezing rain		
0° - 15° 个↓	Snow	Plow, treat with blends, sand hazardous areas	Not recommended	300 - 400	Not recommended	500 - 750 spot treatment as needed		
< 0°	Snow	Plow, treat with blends, sand hazardous areas	Not recommended	400 - 600**	Not recommended	500 - 750 spot treatment as needed		

^{*} Dry salt is not recommended. It is likely to blow off the road before it melts ice.

^{**} A blend of 6 - 8 gal/ton ${\rm MgCl_2}$ or ${\rm CaCl_2}$ added to NaCl can melt ice as low as -10°.

Anti-icing Route Data Form								
Truck Station:								
Date:								
Air Temperature	Pavement Temperature	Relative Humidity	Dew Point	Sky				
Reason for applying:								
Route:								
Chemical:								
Application Time:								
Application Amount:								
Observation (first da	y):							
Observation (after ev	/ent):							
Observation (before	next application):							
Name:								